




SAMSUNG TECHWIN

# Enhanced functionalities, with Full HD video out 8CH, Real-Time @ D1 and above



## 8CH 4CIF Real-time H.264 Digital Video Recorder SRD-873D

The next generation of Samsung's legendary SRD DVR products add Full HD 1080p HDMI video out, support for 650TV lines analog cameras, and a sleek touch sensitive front panel, while retaining the familiar and easy to use graphical interface, smartphone support, coaxitron, tampering detection, and E-mail alerts. The SRD-873D supports real-time, 30/25 frames per second recording and playback at 960 x 480 resolution over all channels. Network bandwidth has also been increased for robust remote viewing at high resolutions.

- 8CH Real-Time @ D1 and 960H resolution
- Max. resolution of 960 x 480 / 960 x 576
- Touch interface front panel
- Coaxitron support
- Smart phone support (Android/iOS)
- Full HD 1080p video out via HDMI
- 8CH audio inputs/1CH audio output
- Max. 4 internal HDDs
- Smart searching, Tampering detection
- Enhanced Network Bandwidth up to 32Mbps

# 8CH 4CIF Real-time H.264 Digital Video Recorder

## SRD-873D




### Specifications

SRD-873D		
Video	Inputs	8 composite video 0.5-1 Vpp, 75 ohm automatic termination
	Resolution	NTSC : 960 x 480, 720 x 480 / PAL : 960 x 576, 720 x 576
Live	Frame Rate	NTSC : 240fps / PAL : 200fps
	Resolution	NTSC : 960 x 480, 720 x 480 / PAL : 960 x 576, 720 x 576
	Multi Screen Display	1/4/7/9/13/PIP/Sequence
<b>PERFORMANCE</b>		
Operating System	Embedded	Linux
	Compression	H.264
Recording	Record Rate	NTSC : Up to 240fps @ 960x480 / PAL : Up to 200fps @ 960x576
		NTSC : Up to 240fps @ 704x480 / PAL : Up to 200fps @ 704x576
	Mode	NTSC : Up to 240fps @ 704x240 / PAL : Up to 200fps @ 704x288
		NTSC : Up to 240fps @ 352x240 / PAL : Up to 200fps @ 352x288
Event	NTSC : Manual, Schedule (Continuous/Event), Event (Pre/Post), Time lapse (1-30 fps)	
Search & Playback	Event	PAL : Manual, Schedule (Continuous/Event), Event (Pre/Post), Time lapse (1-25 fps)
	Overwrite Modes	Video Loss, Motion (Level 1-10), Alarm, Tampering (Level 1-3)
	Pre-alarm	Continuous
	Post-alarm	Up to 30 sec (5,10,20,30 Sec)
Search & Playback	Search Mode	Up to 6 hour (5,10,20,30 sec,1,3,5,10,20 min,1.2,3,4,5,6 hour)
	Playback Function	Date/time, Event, Back up, POS, Motion (* All search include preview function)
Network (IPv4)	Transmission Speed	Fast Forward/Backward (x2,x4,x8,x16,x32,x64) * Backward Play with I-frame Only,
	Bandwidth	Slow Forward/Backward (x1/2,x1/4,x1/8)
	Bandwidth Control	Step Forward/Backward (x2, x4,x8,x16,x32,x64) * Backward Play with I-frame Only
	Stream	4CIF/2CIF/CIF (120/240/240fps NTSC, 100/200/200fps PAL)
Smart phone	Max. Remote Users	Up to 32Mbps
	Protocol Support	Selectable
	Monitoring	H.264 (4CIF/2CIF/CIF Selectable)
	Platform	Search (3) / Live Unicast (10) / Live Multicast (20)
Storage	Protocol Support	TCP/IP, DHCP, PPPoE, SMTP, NTP, HTTP, DDNS, RTP, RTSP, SNMP
	Max. Remote Users	Net-I Viewer, Smart viewer, Webviewer
	Internal HDD	Android, iOS
	External (e-SATA Interface)	RTP, RTSP, HTTP, CGI
Security	DVD Writer (Back up)	Live (1)
	USB (Back up)	Up to 4 SATA HDDs
	File Format (Back up)	Up to 2 expansion bay (* Model : SVS-5R/5E)
INTERFACE	Password Protection	Yes
	Data Authentication	1 Admin, 10 Group, 10 User per 1 Group
Monitors	VGA	Watermark
	HDMI	1 VGA (1280x720, 1280x1024, 1920x1080)
Audio	Spot (Composite)	1 HDMI (1280x720, 1280x1024, 1920x1080)
	Inputs/Output	Digital spot (2CH) * Included OSD on screen, Multi mode support (1CH)
Alarm	Compression	8CH line in (Built in 4CH, Option : Audio extension cable) / 1CH line out
	Sampling Rate	G.711
Connections	Inputs/Outputs	8KHz
	Remote Notification	Terminal 8 Inputs (NO/NC) / Terminal 4 relay Outputs (NO/NC), Rating : 30V DC/2A, 250V AC/0.25A
GENERAL	Ethernet	Notification via e-mail
	Serial Interface	1 RJ45 10/100/1000 Base-T
	USB	RS-232/RS-485 for PTZ, Samsung System Keyboard
	e-SATA	RS-232/RS-485 for PTZ, Samsung System Keyboard
Electrical	Application Support	USB 2.0, 2 ports
	Input Voltage/Current	2 External SATA ports
Environmental	Power Consumption	Mouse, Remote controller
	Operating Temperature/Humidity	Samsung-T/E, Pelco-D/P / Panasonic / Phillips / AD / DIAMOND / ERNA / KALATEL / VCL TP / VICON / ELMO / GE
Mechanical	Dimension (W x H x D)	PTZ control via coaxial cable (Samsung CCVC, Pelco-C (Coaxitron))
	Weight (With hard disks)	Approx. 5.2 kg (11.46 lb)
Language	Rack Mount Kit	2 EA
		Korean, Japanese, Chinese (Simplified/Traditional), English, French, German, Spanish, Italian, Russian, Polish, Czech, Turkish, Netherlands, Portuguese, Swedish, Danish, Thai, Romanian, Serbian, Croatian, Hungarian, Greek, Chinese, Finnish, Norwegian (25 Language)

### Dimensions

Unit : mm (inch)



The Eco mark represents Samsung Techwin's will to create environment-friendly products, and indicates that the product satisfies the EU RoHS Directive.

Design and specifications are subject to change without notice.

■ DISTRIBUTED BY



#### SAMSUNG TECHWIN CO., LTD.

701, Sampyeong-dong, Bundang-gu, Seongnam-si, Gyeonggi-do Korea 463-400  
Tel : +82-70-7147-8741-8749, 8752-8760 Fax : +82-31-8018-3745  
www.samsungsecurity.com www.samsungcctv.com

#### SAMSUNG TECHWIN AMERICA Inc.

1480 Charles Willard St, Carson, CA 90746, UNITED STATES  
Tel Free : +1-877-213-1222 Fax : +1-310-632-2195  
www.samsungcctvusa.com

#### SAMSUNG TECHWIN EUROPE LTD.

Samsung House, 1000 Hillwood Drive, Hillwood Business Park  
Chertsey, Surrey, UNITED KINGDOM KT16 0PS  
Tel : +44-1932-45-5300 Fax : +44-1932-45-5325

#### SHANGHAI SAMSUNG TECHWIN CO., LTD.

32F, BIK B, International Business Center, No. 391  
Guiping Rd, Shanghai, China, 200233  
Tel : +86-21-5427-1155 Fax : +86-21-5423-5122



**SAMSUNG TECHWIN**