

Expanding, Extracting, Flaring

System Overview

Expander Heads

Expander Head Standard



Expander Head ROLOCK



Expander Head Type S



Riveted Expander Head



Working range: Copper	Ø 8-42 mm (5/16-1.3/4") +Ø 1,6 mm, soft, smi-hard	Ø 8-42 mm (5/16-1.3/4") +Ø 1,6 mm, soft, semi-hard	Ø 22-67 mm (1-2.1/2") +Ø 2,5 mm, soft, semi-hard	Ø 15-38 mm +Ø 1,5 mm, soft, semi-hard
Working range: Aluminium	Ø 8-28 mm (5/16-1.1/8") +Ø 1,6 mm, soft	Ø 8-28 mm (5/16-1.1/8") +Ø 1,6 mm, soft	Ø 22-67 mm (1-2.1/2") +Ø 2,5 mm, soft	Ø 15-28 mm +Ø 1,5 mm, soft
Working range: Precision steel	Ø 8-28 mm (5/16-1.1/8") +Ø 1,6 mm, soft	Ø 8-28 mm (5/16-1.1/8") +Ø 1,6 mm, soft	Ø 22-54 mm (1-2.1/8") +Ø 1,5 mm, soft	Ø 15-28 mm +Ø 1,5 mm, soft
Working range: Stainless steel	Ø 8-22 mm (5/16-7/8") +Ø 1 mm, soft	Ø 8-22 mm (5/16-7/8") +Ø 1 mm, soft	Ø 22-54 mm (1-2.1/8") +Ø 1,5 mm, soft	Ø 15-22 mm +Ø 1,0 mm, soft
Page	84	85	87	87

Expander Head H2, Type 2



Expander Head H2, Type 3



Step Expander Head



Working range: Copper	Ø 28-70 mm (1.1/8-2.3/4") +Ø 2,5 mm, soft, semi-hard	Ø 70-110 mm (2.3/4-4.1/4") +Ø 3,0 mm, soft, semi-hard	Ø 35-108 mm (1.3/8-4.1/8") +Ø 2,5 mm, soft, semi-hard
Working range: Aluminium	Ø 28-70 mm (1.1/8-2.3/4") +Ø 2,5 mm, soft, semi-hard	Ø 70-110 mm (2.3/4-4.1/4") +Ø 3,0 mm, soft, semi-hard	Ø 35-108 mm (1.3/8-4.1/8") +Ø 2,5 mm, soft
Working range: Precision steel	Ø 28-70 mm (1.1/8-2.3/4") +Ø 2,5 mm, soft, semi-hard	Ø 70-110 mm (2.3/4-4.1/4") +Ø 3,0 mm, soft, semi-hard	–
Working range: Stainless steel	Ø 28-70 mm (1.1/8-2.3/4") +Ø 2,5 mm, soft, semi-hard	Ø 70-110 mm (2.3/4-4.1/4") +Ø 3,0 mm, soft, semi-hard	–
Page	92	92	88