
ELBOWS

ELBOWS



The LOKRING elbows are made from copper tube in accordance with EN 12735-1and suitable for an operating pressure up to 50 bar (725 psi).

ELBOWS

90° COPPER ELBOWS



- $\begin{tabular}{ll} \end{tabular} \begin{tabular}{ll} \end{tabular} \beg$
- $\ensuremath{\bigodot}$ In accordance with EN 12735-1.
- → Max. operating pressure: 50 bar (725 psi)

Article no.	Article name	Oute [mm	r-ø "]
L13005952	LOKRING Cu 90-EB 9,53	9.53	3/8
L13005953	LOKRING Cu 90-EB 12,7	12.7	1/2
L13005954	LOKRING Cu 90-EB 16	16	5/8
L13005955	LOKRING Cu 90-EB 19	19	3/4
L13005956	LOKRING Cu 90-EB 22	22	7/8
L13005957	LOKRING Cu 90-EB 28,6	28.6	1 1/8
L13005958	LOKRING Cu 90-EB 35	35	1 3/8

45° COPPER ELBOWS



- igoplus Supplied with the necessary stabilisation inserts.
- → Max. operating pressure: 50 bar (725 psi)

	Article name	Outer-ø
		[mm "]
L13005959	LOKRING Cu 45-EB 9,53	9.53 3/8
L13005960	LOKRING Cu 45-EB 12,7	12.7 1/2
L13005961	LOKRING Cu 45-EB 16	16 5/8
L13005962	LOKRING Cu 45-EB 19	19 3/4
L13005963	LOKRING Cu 45-EB 22	22 7/8
L13005964	LOKRING Cu 45-EB 28,6	28.6 1 1/8
L13005965		35 13/8