



iGuard Series

Compact UPS for SOHO and Office Automation

- Reliable & durable housing design
- High frequency technology design
- High reliability
- Pro-active audible warning
- Modem/Network surge protection (RJ45)
- Quick installation & easy operation
- User friendly hotswappable and replaceable battery design
- Provide full protection

NEUROPOWER™

A Preferred Power Solutions Strategic Business Partner

iGuard Series

700VA

Technical Specification

Model	i-Guard 700	
Power Rating	Total Rating	1000VA
	Battery Mode	700VA
Input	Range	170V - 280V
	Frequency	50/60Hz
	Phase	Single, 2 wires + ground
Output (Battery Mode)	Voltage	220/230/240VAC +/- 10%
	Frequency	50 or 60Hz +/- 1Hz
	Waveform	Simulated sinewave
Outlets	(4) British sockets (1 x surge protection, 3 x surge with battery backup)	
Transfer Time	Typical	2 – 6 ms
Battery	Battery Type	Seal lead acid maintenance free
	Rating	(1) 12V 7.2AH
	Recharge time	10 hours up to 90% capacity
Backup Time*	Full Load	8 - 10 min typically
Display	LED	Power-On, backup mode & fault
Audible Alarm	Battery Mode	Beeping every 5 sec
	Low Battery	Beeping every 1 sec
	Overload	Beeping every 0.5 sec
	Fault	Continuous beeping
Protection	Input	User resettable breaker
	Standard	Overload, overcharge, short circuit
	Modem/Network	Surge protection (RJ45)
Power Management	Interface Port	USB
Environment	Temperature	0° to 40°C
	Humidity	Up to 90% without condensation
Physical	Dimension, W x D x H (mm)	124 x 202 x 166
	Weight (kg)	4.3

- 3 years warranty for electronics parts, 2 years warranty for the battery against manufacturing defects.
- Backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.*
- In the interests of continuous product improvement, all specifications are subject to change without notice.

