

## CNC-4313-M-II – 2MP Motorized IR IP Dome



### Features

- Up to 2 Megapixel @25fps
- **H.265+** Compression
- ONVIF compatible
- **2.8-12mm Motorized** Lens
- 120dB **True WDR**
- 3D-DNR, BLC, DSS
- Day&Night by Filter Change (TDN)
- IR LEDs, 0 Lux up to 30m
- SMART-IR
- Build-In SD Card Slot up to 128GB
- **Vandal Resistant**
- Smart : Line Crossing & Intrusion
- Audio+Alarm (Optional)

### SPECIFICATION

Model	CNC-4313-M-II
Image Sensor	1/2.8" progressive scan CMOS Sensor
Resolution	50Hz 1920x1080 @25fps
Shuttle	1/3s ~ 1/100,000s
Lens	2.8~12mm Motorized Lens
Illumination	30m 850nm IR LEDs
Day & Night	Filter Change or TDN (True Day & Night)
Min. Illumination	0 Lux up to 30m
Network	10/100-BaseT, RJ45
Bit Rate	32Kbps ~ 16Mbps
Compression	Dual Stream : H.265+ / H.264+
W. Environment	-30° ~ +60°C, <90° Humidity (Non-Condensing)
Power	POE 802.3af, or 12VDC, Max. 12W (IR-On)
Dimension	154mm(φ) x 112mm(H), 880g

