

## CNC4535 – 4M WDR 50m IR Weatherproof Camera



**4 Mega**

**50m LED Array**

**WDR**

**TDN**

**3D-DNR**

**IP67**

**Dual Stream**

**POE**

**ONVIF**

### Features

- 4 Megapixel 2688x1520 @20fps
- H.264+, ONVIF
- 12VDC / POE Dual Power
- 6mm Fixed Lens
- 120dB True WDR
- 3D-DNR, Dual Stream, ROI
- Day&Night by Filter Change
- 0 Lux up to 50m
- Network 10/100 Base-T
- Line Crossing / Intrusion Detection
- Android, iPhone/iPad application
- IE & 64ch CMS Software included
- IP67 Weatherproof

### SPECIFICATION

Model	CNC4535
Image Sensor	1/3" progressive scan CMOS Sensor
Resolution	50Hz 2688x1520 @20fps / 1920x1080 @25fps
Shuttle	1/25s ~ 1/100,000s
Lens	M12 6mm Fixed Lens
LEDs	2nos 3W High Power LED Array
Day & Night	Filter Change or TDN (True Day & Night)
Minimum Illumination	0 Lux up to 50m
Network	10/100-BaseT, RJ45
Bit Rate	32Kbps ~ 16Mbps
Compression	Dual Stream : H.264+ / MJPEG / H.264
Working Environment	-10° ~ +60°C, <90° Humidity (Non-Condensing)
Power	POE IEEE 802.3af compliant, or 12VDC, Max. 7.5W (IR-On)
Dimension	86.5mm(V) x 85.1mm(W) x 300mm(L), 1.2kg

\* Specification maybe changed without prior notice