

Chainsaw Protection

Chainsaw Chap

Multi-layered Kevlar® with Cordura® nylon outer shell. Two-inch wide heavy nylon belt with adjustable quick release Nexus® clip. Fivecompartment tool pocket with snap flap closure. Designed to clog and block the cutting chain. Added protection is provided if the Kevlar® material is pulled into the drive sprocket, jamming it. Chap is not a substitute for safe operating procedures. It is the buyer's responsibility to determine if this product will be adequate protection.

Measure length from waist down.

2600-28" 2600-36" 2600-32" 2600-40"

Metatarsal Guard



LW-800

Wear with steel toe safety shoes to extend impact protection to instep. Aluminum alloy with rubber padding.



Foot Guard



LW-200

Protect entire front of foot from impact hazards. Aluminum alloy, rubber strap, rubber toe clip.

Chainsaw Gloves

CSG-3

Grain pig leather palm. Back is 1-ply Kevlar® jersey and 3-ply ballistic Kevlar®.

Available in sizes XS-XL.



Steel Toe Guards



LW-702

Steel guard for maximum toe protection. Quick fastener, adjustable web strap.

Shin Guard



LW-303

Aluminum alloy, padded top and bottom, fastened with web straps.

Shin-Instep Guard



LW-323

Aluminum alloy, padded with sponge rubber. Fastened with web straps.

Knee-Shin-Instep Guard



LW-334

Plastic, padded with sponge rubber. Fastened with web straps.

Plastic Toe Guard



LW-505

Lightweight toe protection. Does not replace steel toe shoe protection.