

TROLLEYS

A multifunctional modular system with the approved fetra Insert-and-Bolt Principle • The MultiVario-Transporter can be altered, interchanged and supplemented in many ways • Stylish frame structure of „one cast“ with „round edges“ • The system components are simply inserted into the basic element and bolted tight • An absolutely secure connection of frames and superstructures • High quality powder coating blue RAL 5007 • Derived timber material boards housed in the frame, surface beech grain • 2 swivel and 2 fixed-wheel castors, wheels with TPE tyres, hubs with groove ball bearing • Swivel castors with wheel locks





TROLLEYS



2500 | 2501 | 2502 | 2503



2500B | 2501B | 2502B | 2503B



2580 | 2581 | 2582 | 2583



2590 | 2591 | 2592 | 2593



MultiVario
Insert-and-Bolt Principle



Waterproof and more
platforms
for MultiVario transporters
(for details see page 169)

MultiVario-Transporter Modular system

The MultiVario-Transporter can be altered, interchanged and supplemented in many ways. The system components are simply inserted into the basic element 2590-2593 and bolted tight.

Tubular steel and profile steel welded, powder coated, surface durably protected, resistant to impact and scratches. Platform made of derived timber material boards, surface beech design.

2 swivel and 2 fixed-wheel castors, TPE tyres, 160 x 40 or 200 x 40 mm, hubs with groove ball bearing or pneumatic tyres 220 x 70 mm (additional charge).

Swivel castors with wheel locks, according to the European Standard EN 1757-3 (safety of platform trolleys).

Height of loading platform:

TPE 160 Ø = 228 mm

TPE 200 Ø = 270 mm

Pneumatic tyres 220 Ø = 285 mm

Open carts 2500B-2503B

Platform made of sheet steel, flush with frame, welded, powder coated RAL 5007.

Stanchioned trolleys 2580-2583

Stanchions 693/640 mm long

Accessories MultiVario

- Wheels with pneumatic tyres
- Wheels with TPE-ESD tyres
- Polyamide wheels
- Wheels with polyurethane tyres
- 4 swivel castors
- Protective edge
- Protective wheels
- Clip board and wire basket
- Softgrip push handle
- Dead man brake
- Collapsible push handle
- Electric drive unit
- Scanner holder
- Waterproof platforms
- PVC panel
- Scoring rubber

Accessories
on pages 168-170

	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Outside dimensions L x W x H mm	Net weight kg
Open carts	2500	500	160	850 x 500	975 x 509 x 948	24
	2501	600	200	1000 x 600	1125 x 609 x 990	28
	2502	600	200	1000 x 700	1125 x 709 x 990	30
	2503	600	200	1200 x 800	1325 x 809 x 990	35
Open carts with platform made of sheet steel	2500B	500	160	850 x 500	975 x 509 x 948	28
	2501B	600	200	1000 x 600	1125 x 609 x 990	34
	2502B	600	200	1000 x 700	1125 x 709 x 990	36
	2503B	600	200	1200 x 800	1325 x 809 x 990	45
Stanchioned trolleys	2580	500	160	850 x 500	1100 x 509 x 923	25
	2581	600	200	1000 x 600	1250 x 609 x 960	29
	2582	600	200	1000 x 700	1250 x 709 x 960	31
	2583	600	200	1200 x 800	1450 x 809 x 960	36
Platform trolleys	2590	500	160	850 x 500	919 x 509 x 228	21
	2591	600	200	1000 x 600	1069 x 609 x 270	25
	2592	600	200	1000 x 700	1069 x 709 x 270	27
	2593	600	200	1200 x 800	1269 x 809 x 270	33

Blue marked item numbers = quick delivery (for details see page 4)



TROLLEYS



MultiVario-Transporter Modular system

The MultiVario-Transporter can be altered, interchanged and supplemented in many ways. The system components are simply inserted into the basic element 2590-2593 and bolted tight.

Tubular steel and profile steel welded, powder coated, surface durably protected, resistant to impact and scratches. Platform made of derived timber material boards, surface beech design.

2 swivel and 2 fixed-wheel castors, TPE tyres, 160 x 40 or 200 x 40 mm, hubs with groove ball bearing or pneumatic tyres 220 x 70 mm (additional charge).

Swivel castors with wheel locks, according to the European Standard EN 1757-3 (safety of platform trolleys).

Height of loading platform:

TPE 160 Ø = 228 mm
TPE 200 Ø = 270 mm
Pneumatic tyres 220 Ø = 285 mm

Panelled end platform carts Double open side platform carts

2510-2513 | 2520-2523

Panelled end made of derived timber material boards, surface beech grain.

End panel height: 500 mm

Open sided platform carts Closed platform carts

2530-2533 | 2550-2553

Panelled ends and panelled sides made of derived timber material boards, surface beech grain.

End panel height: 500 mm
Side panel height: 500 mm

Closed platform cart with one detachable side panel.

Accessories
on pages 168-170



2510 | 2511 | 2512 | 2513



2520 | 2521 | 2522 | 2523



2530 | 2531 | 2532 | 2533



2550 | 2551 | 2552 | 2553



	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Outside dimensions L x W x H mm	Net weight kg	
Panelled end platform carts	2510	500	160	850 x 500	970 x 509 x 948	26	
	2511	600	200	1000 x 600	1120 x 609 x 990	31	
	2512	600	200	1000 x 700	1120 x 709 x 990	33	
	2513	600	200	1200 x 800	1320 x 809 x 990	39	
Double open-side platform carts	2520	500	160	850 x 500	1030 x 509 x 948	30	
	2521	600	200	1000 x 600	1180 x 609 x 990	36	
	2522	600	200	1000 x 700	1180 x 709 x 990	40	
	2523	600	200	1200 x 800	1380 x 809 x 990	46	
Open sided platform carts	2530	500	160	850 x 500	1030 x 509 x 948	36	
	2531	600	200	1000 x 600	1180 x 609 x 990	42	
	2532	600	200	1000 x 700	1180 x 709 x 990	45	
	2533	600	200	1200 x 800	1380 x 809 x 990	54	
Closed platform carts	2550	500	160	850 x 500	1030 x 509 x 948	41	
	2551	600	200	1000 x 600	1180 x 609 x 990	47	
	2552	600	200	1000 x 700	1180 x 709 x 990	51	
	2553	600	200	1200 x 800	1380 x 809 x 990	59	



TROLLEYS



1510 | 1511 | 1512 | 1513



1520 | 1521 | 1522 | 1523



1530 | 1531 | 1532 | 1533



1550 | 1551 | 1552 | 1553

MultiVario-Transporter Modular system

The MultiVario-Transporter can be altered, interchanged and supplemented in many ways. The system components are simply inserted into the basic element 2590-2593 and bolted tight.

Tubular steel and profile steel welded, powder coated, surface durably protected, resistant to impact and scratches. Platform made of derived timber material boards, surface beech design.

2 swivel and 2 fixed-wheel castors, TPE tyres, 160 x 40 or 200 x 40 mm, hubs with groove ball bearing or pneumatic tyres 220 x 70 mm (additional charge).

Swivel castors with wheel locks, according to the European Standard EN 1757-3 (safety of platform trolleys).

Height of loading platform:

TPE 160 Ø = 228 mm

TPE 200 Ø = 270 mm

Pneumatic tyres 220 Ø = 285 mm

Panelled end platform carts Double open side platform carts 1510-1513 | 1520-1523

Ends made of wire lattice 50 x 50 x 4 mm.

End panel height: 500 mm

Open sided platform carts Wire cage carts 1530-1533 | 1550-1553

Ends and sides made of wire lattice 50 x 50 x 4 mm.

Height of ends: 500 mm
Height of sides: 500 mm

Wire cage cart with one detachable side.



	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Outside dimensions L x W x H mm	Net weight kg	
Panelled end platform carts	1510	500	160	850 x 500	970 x 509 x 948	25	
	1511	600	200	1000 x 600	1120 x 609 x 990	30	
	1512	600	200	1000 x 700	1120 x 709 x 990	32	
	1513	600	200	1200 x 800	1320 x 809 x 990	37	
Double open-side platform carts	1520	500	160	850 x 500	1030 x 509 x 948	29	
	1521	600	200	1000 x 600	1180 x 609 x 990	34	
	1522	600	200	1000 x 700	1180 x 709 x 990	35	
	1523	600	200	1200 x 800	1380 x 809 x 990	42	
Open sided platform carts	1530	500	160	850 x 500	1030 x 509 x 948	33	
	1531	600	200	1000 x 600	1180 x 609 x 990	38	
	1532	600	200	1000 x 700	1180 x 709 x 990	40	
	1533	600	200	1200 x 800	1380 x 809 x 990	47	
Wire cage carts	1550	500	160	850 x 500	1030 x 509 x 948	36	
	1551	600	200	1000 x 600	1180 x 609 x 990	42	
	1552	600	200	1000 x 700	1180 x 709 x 990	45	
	1553	600	200	1200 x 800	1380 x 809 x 990	52	

Accessories
on pages 168-170



TROLLEYS



Box carts

2560 | 2561 | 2562 | 2563

Ends and sides made of derived timber material boards, Height of sides 250 mm. All sides singly detachable.

Interior width = platform width – 60 mm



2560 | 2561 | 2562 | 2563

Side frame carts

1580 | 1581 | 1582 | 1583

Height of side frames 720 mm

Interior width = platform width – 60 mm



1580 | 1581 | 1582 | 1583

Bale trolleys

2541 | 2542 | 2543

Sides made of derived timber material boards, surface beech grain.

Height of sides 620/750 mm

Interior width = platform width – 60 mm



2541 | 2542 | 2543

Bale trolleys

2571 | 2572 | 2573

2 tubular steel side frames with intermediate uprights at intervals of approx. 130 mm.

Height of sides 750 mm

Interior width = platform width – 60 mm



2571 | 2572 | 2573



	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x B mm	Outside dimensions L x W x H mm	Net weight kg
Box carts	2560	500	160	850 x 500	970 x 509 x 948	34
	2561	600	200	1000 x 600	1120 x 609 x 990	39
	2562	600	200	1000 x 700	1120 x 709 x 990	41
	2563	600	200	1200 x 800	1320 x 809 x 990	49
Side frame carts	1580	500	160	850 x 500	910 x 509 x 948	28
	1581	600	200	1000 x 600	1060 x 609 x 990	32
	1582	600	200	1000 x 700	1060 x 709 x 990	34
	1583	600	200	1200 x 800	1260 x 809 x 990	40
Bale trolleys	2541	600	200	1000 x 600	1060 x 609 x 1025	45
	2542	600	200	1000 x 700	1060 x 709 x 1025	47
	2543	600	200	1200 x 800	1260 x 809 x 1025	55
	2571	600	200	1000 x 600	1060 x 609 x 1025	39
	2572	600	200	1000 x 700	1060 x 709 x 1025	41
	2573	600	200	1200 x 800	1260 x 809 x 1025	49

Accessories on pages 168-170