

# OFFICE- | CATERING- | STAINLESS STEEL TROLLEYS

A clear design • Extremely easy to handle • Large quality castors, 2 of them with total locking units • Proven screw construction, disassembled delivery in a cardboard box • Easy self-assembly • Office trolleys consisting of steel tubing • Powder-coating light grey RAL 7035 • Floors and walls consisting of light grey wood-based shelves • Catering trolleys consisting of steel tubing • Powder-coated in white aluminium RAL 9006 • Removable laminate trays or solid shelves consisting of anthracite-grey wood-based shelves • Ideal for use in dry areas • Stainless-steel trolleys consisting of CNS • Stainless and durable • Thermoformed shelves with edge, sound-absorbing lining • Ideal for use in damp and wet areas







4870 | 5001 | 5042

# **OFFICE TROLLEYS**



4870





# 4872





	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Outside dimensions L x W x H mm	Shelf heights mm	Net weight kg	
Office trolleys light grey/ pale grey	4870	150	125	720 x 350	810 x 385 x 1100	260, 620, 980	22	
	4871	150	125	720 x 350	810 x 385 x 1100	260, 620, 980	25	
	4872	150	125	720 x 350	810 x 385 x 1100	260, 620, 980	23	
	4873	150	125	720 x 350	810 x 385 x 1100	260, 620, 980	26	
	4878	150	125	1080 x 350	1165 x 385 x 1100	260, 620, 980	34	

### Office trolleys

in a bolted, tubular steel construction, powder coated light grey RAL 7035. Shelves and panels made of derived material timber board, pale grey.

4 swivel castors, pneumatic tyres 125 x 32 mm, hubs with roller bearings, trackless.

2 tyres with wheel locks, according to the European Standard EN 1757-3 (safety of platform trolleys).

Flat packed for easy self assembly.

Capacity per shelf 50 kg.

### 4871

With longitudinal wall (back wall).

### 4872

With separating plate.

### 4873

With separating plate and longitudinal wall (back wall).

### 4878

With 2 separating plates and longitudinal wall (back wall).



### Office trolleys

in a bolted tubular steel construction, powder coated light grey RAL 7035. Shelves and panels made of derived material timber board, pale grey.

4 swivel castors, pneumatic tyres 125 x 32 mm, hubs with roller bearings, trackless.

2 tyres with wheel lock, according to the European Standard EN 1757-3 (safety of platform trolleys).

Flat packed for easy self assembly.

### 4880 | 4882

Capacity per shelf 50 kg.

### 4891

with shelves inclined to the rear. Back wall in a right angle to the shelf.

Inclination approx. 27 mm. Capacity per shelf 50 kg. With back wall.

# **OFFICE TROLLEYS**











	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Outside dimensions L x W x H mm	Shelf heights mm	Net weight kg	
Office trolleys	4880	150	125	800 x 500	900 x 535 x 925	260, 800	19	
	4882	150	125	800 x 500	900 x 535 x 925	260, 530, 800	24	
	4891	150	125	770 x 320	855 x 400 x 1218	246, 606, 966	31	