

## SHEET MATERIAL TRANSPORT

Dollies for sheet material • Carts for sheet material • For longitudinal transport of bulky wooden boards and plastic sheets • Trolleys for sheet material • Stands for sheet material • The suitable product matches the respective application pupose • Neatly welded sectional/tubular steel construction • Powder coated blue RAL 5007 – high-quality and durable • With solid rubber or pneumatic tyres • TPE tyres • Elastic solid rubber tyres, blue-grey „trackless“ for heavy loads • 250 – 1200 kg capacity



4463 | 3012 | 6012 | 9012



## DOLLIES FOR SHEET MATERIAL



4155 | 4156



4157 | 4158



4165 | 4166



4175 | 4176



Example of use

### Dollies for sheet material 4155 | 4156

Dolly for sheet material with clamping jaws. Steel-welded construction, powder coated blue RAL 5007.

Jaw surface with felt coating. Wheels with either solid rubber or pneumatic tyres, hubs with roller bearings.

Secure clamping by the weight of the load on the clamping construction. Maximal clamping width: 0-60 mm

### 4157 | 4158

As 4155 | 4156, but clamping width 30-95 mm (suitable for windows).

### Dollies for sheet material 4165 | 4166

Dolly for sheet material in U-form. Steel sheet construction, powder coated blue RAL 5007, interior surface with felt coating.

Wheels with either solid rubber or pneumatic tyres, hubs with roller bearings.

Clear width: 150 mm

### 4175 | 4176

Dolly for sheet material as 4165 | 4166, but with support and push bar.

Clear width: 150 mm

	Order no.	Capacity kg	Height mm	Lifting blade length mm	Lifting blade width mm	Total width mm	Solid rubber tyres mm	Pneumatic tyres mm	Net weight kg
Dollies for sheet material	4155	250	300	300	60	305	250 x 60	-	8
	4156	250	310	300	60	305	-	260 x 85	6
	4157	250	300	300	95	340	250 x 60	-	8
	4158	250	310	300	95	340	-	260 x 85	6
	4165	500	250	500	150	380	250 x 60	-	8
	4166	400	260	500	150	380	-	260 x 85	6
	4175	500	900	500	150	380	250 x 60	-	10
	4176	400	910	500	150	380	-	260 x 85	8



## CARTS



### Carts for sheet material 1075 | 1076

Carts for longitudinal transport of bulky wooden boards and plastic sheets. Tubular steel construction with steel sheet blade, powder coated blue RAL 5007.

Wheels with either solid rubber or pneumatic tyres. Hubs with roller bearings.

2 support wheels 50 mm Ø.

Flat packed delivery.

### 2075 | 2076

Cart for sheet material as 1075 | 1076 but fitted with rubber strip (nonskid).

With holding-down clamp as tilt lock.



1075 | 1076



2075 | 2076



Example of use

	Order no.	Capacity kg	Height mm	Lifting blade length mm	Lifting blade width mm	Total width mm	Solid rubber tyres mm	Pneumatic tyres mm	Net weight kg
Carts for sheet material	1075	400	1430	500	200	680	250 x 60	-	18
	1076	350	1440	500	200	680	-	260 x 85	16
	2075	400	1450	500	200	680	250 x 60	-	20
	2076	350	1460	500	200	680	-	260 x 85	18

Blue marked item numbers = quick delivery (for details see page 4)



# TROLLEYS FOR SHEET MATERIAL



4411 | 4412 | 4413



4445



4463 | 4463-1 | 4465 | 4465-1



Pallet feet 2021



4363 | 4365

## Trolleys for sheet material

4411 | 4412 | 4413

With fixed tubular supports. Tubular steel and profile steel welded, powder coated blue RAL 5007. Platform made of derived timber material board, surface beech grain. Bolted tubular steel superstructure. 2 swivel and 2 fixed-wheel castors, TPE tyres, hubs with groove ball bearing. Swivel castors with wheel locks.

Effective height: 1050 mm  
Height retaining bracket: 300 mm

4445

Welded profile steel and steel tube. Anti-skid loading platform of waterproof plywood.

2 swivel and 2 fixed-wheel castors, TPE tyres, hubs with groove ball bearing. Swivel castors with wheel locks.

Effective height: 1150 mm

4463 | 4463-1

4465 | 4465-1

Up to 1200 kg capacity

Welded sectional and tubular steel, powder coated, with wooden platform. 7 positions for insertable tubular supports. Clearance between supports 90 mm.

2 castor wheels and 2 fixed wheels, castors wheels with wheel lock.

750 kg = TPE tyres, hubs with groove ball bearing

1200 kg = elasticated solid-rubber tyres, blue-grey „trackless“, hubs with ball bearings.

Loading height: 295 mm

## Sheet material stands

4363 | 4365

1200 kg capacity

Welded sectional and tubular steel, powder coated, with wooden platform. 4 rubber feet. 7 positions for insertable tubular supports. Delivery without tubular supports. Clearance between tubular supports 90 mm.

One face end fitted with 6-piece pick-up roller.

## Pallet feet 2021

As accessory for sheet material stands. Access 100 mm, for pallet truck or fork-lift access.

## Accessories

on pages 168-170

	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Outside dimensions L x W x H mm	Net weight kg
Sheet material trolleys with fixed tubular supports	4411	600	200	1070 x 335	1070 x 610 x 1321	36
	4412	600	200	1070 x 435	1070 x 710 x 1321	41
	4413	600	200	1270 x 535	1270 x 810 x 1321	45
Trolley for sheet material	4445	500	200	1500 x 400	1500 x 710 x 1510	59
Sheet material trolleys for insertable tubular supports (without tubular supports)	4463	750	200	1200 x 800	1320 x 800 x 295	54
	4463-1	1200	200	1200 x 800	1320 x 800 x 295	59
	4465	750	200	1600 x 800	1720 x 800 x 295	60
	4465-1	1200	200	1600 x 800	1720 x 800 x 295	66
Sheet material stands (without tubular supports)	4363	1200	-	1200 x 800	1365 x 800 x 100	45
	4365	1200	-	1600 x 800	1765 x 800 x 100	51
Insertable tubular supports for sheet material trolleys 4463   4463-1 4465   4465-1 and for sheet material stands 4363   4465	3012	1200		Length mm	Height mm	Net weight kg
	6012	1200		1200	300	5
	9012	1200		1200	600	6
	3016	1600		1600	300	6
	6016	1600		1600	600	7
9016	1600		1600	900	8,5	
Pallet feet	2021			-	-	6



## TROLLEYS FOR SHEET MATERIAL



### Glass panel trolleys and trolleys for sheet material

for safe transport of glass panels, wood or plastic panels as well as complete windows or doors.

Trolleys for sheet material. Welded sectional and tubular steel. Powder coated blue RAL 5007.

2 swivel and 2 fixed-wheel castors, elasticated solid rubber tyres, blue-grey „trackless“, hubs with ball bearings.

Swivel castors with wheel locks, according to the European Standard EN 1757-3 (safety of platform trolleys).

For up to 1200 kg capacity.



4454 | 4455 | 4456

### 4454 | 4455 | 4456

One-sided.

Fitted with rubber strip on one side only.

### 4474 | 4475 | 4476

Double-sided.

Fitted with rubber strip on two sides.



4474 | 4475 | 4476

	Order no.	Capacity kg	Wheel-Ø mm	Outside dimensions L x W x H mm	Loading surface L x W mm	Support height mm	Charge kg
Sheet material trolleys (one-sided)	4454	1200	200	1276 x 800 x 1788	1276 x 430	1450	63
	4455	1200	200	1676 x 800 x 1788	1676 x 430	1450	71
	4456	1200	200	2076 x 800 x 1788	2076 x 430	1450	96
Sheet material trolleys (double-sided)	4474	1200	200	1276 x 800 x 1783	1276 x 2x 230	1450	69
	4475	1200	200	1676 x 800 x 1783	1676 x 2x 230	1450	77
	4476	1200	200	2076 x 800 x 1783	2076 x 2x 230	1450	103