



MOBILE TILTING STANDS

5 models • 9 types • Relieves the spine during sitting or standing activities • Neatly welded steel construction • Powder coated blue RAL 5007 • Manual height adjustment in variable steps with safety lock spring catch or steplessly by lifting jack with load or by means of hydraulic pump • Platforms with rim or edge • Tiltable to one side in intervals, except 3270 • 4 swivel castors, wheels with TPE tyres • 2 Swivel castors with wheel locks

MOBILE TILTING STANDS



3285 | 3290



MOBILE TILTING STANDS



Mobile tilting stands

For plastic boxes, steel plate boxes, wire baskets etc., adjustable in height and mobile.

Sectional steel-/ tubular construction with steel plate platform. Powder coated blue RAL 5007. 4 swivel castors with TPE tyres, hubs with bush bearing, 2 wheels with locks.

3260 | 3270

Steel plate platform with all side rim, 20 mm high. Not inclinable, adjustable in height in intervals of 25 mm.



3260



3270

3280 | 3282

Steel plate platform with single-sided lay-on edge, straight or inclinable by 15° und 30°, adjustable in height in intervals of 25 mm.



3280



3282



Example of use

	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Height adjustable from – to mm	Net weight kg
Mobile tilting stands	3260	150	75	605 x 405	524-774	17
	3270	150	75	605 x 405	720 – 995	17
	3280	150	75	510 x 410	500 – 775	18
	3282	150	75	510 x 410	755 – 1105	18

Blue marked item numbers = quick delivery (for details see page 4)



MOBILE TILTING STANDS | ROLLER SUPPORT



3285



3286



3290



3291



3191

Mobile tilting stands

For plastic boxes, steel plate boxes, wire baskets etc., adjustable in height and mobile.

Sectional steel-/ tubular construction with steel plate platform. Powder coated blue RAL 5007. 4 swivel castors with TPE tyres, hubs with bush bearing, 2 wheels with locks.

3285

Steel plate platform with single-sided lay-on edge, straight or inclinable by 15° und 30°, continuously adjustable in height via rack and pinion jack, even under load. 2 telescopic pillars.

3286

Steel plate platform with single-sided lay-on edge, straight or inclinable by 15° und 30°, continuously adjustable in height via hydraulic pump, even under load. Operated via pedal, precisely adjustable via lowering valve.

3290 | 3291

Steel plate platform with single-sided lay-on edge, straight or inclinable by 15° und 30°, continuously adjustable in height, rotatable and lockable, with pneumatic lowering damping.

Roller support

3191

To support long materials on saws, presses, drills etc. Continuously adjustable in height, rotatable and lockable, with pneumatic lowering damping. Mobile. Supporting roller of tubular steel 450 mm, 60 mm Ø, ball bearing mounted. Loose gravity-stops on both sides 20 mm above top edge of roller (automatically turn away for wide work pieces).

4 swivel castors with locks. Flat packed for easy self assembly.

	Order no.	Capacity kg	Wheel-Ø mm	Platform size LxW mm	Height adjustable from - to mm	Net weight kg
Mobile tilting stands	3285	250	125	750 x 450	655 - 1025	35
	3286	250	125	750 x 450	720 - 1080	39
	3290	150	75	510 x 410	510 - 700	23
	3291	150	75	510 x 410	720 - 1070	26
Roller support	3191	150	75	-	780 - 1130	21

Disassembled delivery, easy self-assembly. Warranty for 3286, 3290/3291 and 3191 2 years.