



ALUMINIUM TRUCKS



Aluminium trucks

Aluminium trucks made of tubular aluminium with alu blades, very light and handy to use. Aluminum sheet shovel mountable, therefore exchangeable.

Pneumatic tyres on synthetic rims, hubs with roller bearings.

Curved top bar and transversal struts. For safe transport of circular items such as rolls, cans, buckets etc.

Flat packed delivery.

On request with solid rubber tyres, without surcharge.

When ordering please replace in order no. „L“ by „V“.



A1125L



A1115L



A1116L



A1325L



A1326L



A1330L



A1331L

A1330L | A1331L

With replaceable synthetic rockers.


Wear parts

Handle 1762

With safety loop for tube-Ø 27 mm.

Plastic skids 1753

1 set with clips.



Solid rubber tyres

On request available with solid rubber tyres, without surcharge. Please replace the „L“ with the „V“ at the order number.



Wheel-fixing

screwed wheel fixing, easy wheel change.



Handle 1762

with safety loop for tube-Ø 27 mm.



Plastic skids 1753

1 set with clips.

	Order no.	Capacity kg	Height mm	Blade depth mm	Blade width mm	Total width mm	Pneumatic tyres mm	Net weight kg
Aluminium trucks	A1125L	150	1150	250	320	570	260 x 85	9
	A1115L	150	1150	150	400	590	260 x 85	8
	A1116L	150	1150	300	480	590	260 x 85	9
	A1325L	200	1300	250	320	590	260 x 85	9
	A1326L	200	1300	300	480	590	260 x 85	10
	A1330L	200	1300	250	320	590	260 x 85	9
	A1331L	200	1300	300	480	590	260 x 85	10
Handle	1762	-	-	-	-	-	-	-
Plastic skids	1753	-	-	-	-	-	-	-

Blue marked item numbers = quick delivery (for details see page 4)

Accessories on page 170



STAIRWAY TRUCKS



Stairway trucks

Tubular steel, with lifting blades made of steel sheet, sturdy welded construction, powder coated, blue RAL 5007. Safety handles. Steel sheet front shovel mountable. Flat packed delivery.

Utility patent

20 2004 010 071.1

Curved top bar and transversal struts. For safe transport of circular items such as rolls, cans, buckets etc.

TK1325 | TK1326

With 2 three-armed wheel spiders, each equipped with 3 TPE tyres 160 mm Ø, hubs with ball bearings.

TK1327 | TK1328

With 2 pneumatic tyres on synthetic rims, hubs with roller bearings and 2 five-armed wheel spiders, each equipped with 5 TPE wheels 125 mm Ø, hubs with ball bearings.

Three-arm wheel spider

With 2 three-armed wheel spiders, advantageous for frequent use on stairs and acceptable ground conditions on flat surface.

Five-arm wheel spider

With 2 pneumatic tyres and 2 five-armed wheel spiders, advantageous for frequent use on bad ground conditions on flat surface and occasional use on stairs.

Wear parts

Handle

1762

With safety loop for tube-Ø 27 mm. See page 170.



TK1325



TK1326



TK1327



TK1328



Three-arm wheel spider
TK1325 | TK1326



Five-arm wheel spider
TK1327 | TK1328



Wheel spider lock 1770
Add-on kit for stairway trucks
TK1325 and TK1326. For easy
moving on 2 wheels on flat
surface. Easy self assembly.



Wheel-fixing
screwed wheel fixing, easy
whell change.

	Order no.	Capacity kg	Height mm	Lifting blade depth mm	Lifting blade width mm	Total width mm	TPE tyres mm	Pneumatic tyres mm	Net weight kg
Stairway trucks	TK1325	200	1300	250	320	590	160 x 40	-	18
	TK1326	200	1300	300	480	590	160 x 40	-	22
	TK1327	200	1300	250	320	590	-	260 x 85	20
	TK1328	200	1300	300	480	590	-	260 x 85	22
Wheel spider lock	1770					for TK1325 and TK1326			

Blue marked item numbers = quick delivery (for details see page 4)

Accessories on page 170



STAIRWAY TRUCKS



Aluminium stairway trucks

Aluminium tube with aluminium blades, handy welded construction. Safety handles. Aluminium sheet shovel mountable. Flat packed delivery.

Curved top bar and transversal struts. For safe transport of circular items such as rolls, cans, buckets etc.

AK1325 | AK1326

With 2 three-armed wheel spiders, each equipped with 3 TPE tyres 160 mm Ø, hubs with ball bearings.

AK1327 | AK1328

With 2 pneumatic tyres on synthetic rims, hubs with roller bearings and 2 five-armed wheel spiders, each equipped with 5 TPE wheels 125 mm Ø, hubs with ball bearings.

Three-arm wheel spider

With 2 three-armed wheel spiders, advantageous for frequent use on stairs and acceptable ground conditions on flat surface.

Five-arm wheel spider

With 2 pneumatic tyres and 2 five-armed wheel spiders, advantageous for frequent use on bad ground conditions on flat surface and occasional use on stairs.

Wear parts

Handle 1762

With safety loop for tube-Ø 27 mm. See page 170.

Accessories on page 170



AK1325



AK1326



AK1327



AK1328



Three-arm wheel spider
AK1325 | AK1326



Five-arm wheel spider
AK1327 | AK1328



Wheel spider lock 1770
Add-on kit for stairway trucks
AK1325 and AK1326. For easy
moving on 2 wheels on flat
surface. Easy self assembly.



Wheel-fixing
screwed wheel fixing, easy
wheel change.

	Order no.	Capacity kg	Height mm	Lifting blade depth mm	Lifting blade width mm	Total width mm	TPE tyres mm	Pneumatic tyres mm	Net weight kg
Stairway trucks	AK1325	200	1300	250	320	590	160 x 40	-	14
	AK1326	200	1300	300	480	590	160 x 40	-	15
	AK1327	200	1300	250	320	590	-	260 x 85	15
	AK1328	200	1300	300	480	590	-	260 x 85	16
Wheel spider lock	1770					for AK1325 and AK1326			