

GOLINE

"Plymovent GoLine: where protection against welding fume exposure starts."



GOLINE AND GOLINEPAS

The GoLine and GoLine^{plus} of Plymovent is a range of welding fume extractors that provide effective protection against exposure to welding fume at workplaces where welding is less intensive.

The GoLine, is the entry level extractor for occasional welding applications as where the GoLine^{plus} is suitable for more industrial working environments.

WHY THE GOLINE AND GOLINEPlus

- Excellent price performance
- Effective protection against welding fume exposure
- NEN EN ISO 15012-1:2013/W3 compliant
- Suitable for steel and stainless steel welding applications

MOBILEGO AND MOBILEGO Plus

Compact and powerful mobile welding fume extractors fitted with an extraction arm up to three meter length. The arm can rotate 360° degree and is very easy to handle.

MONOGO AND MONOGO Plus

Single arm fume extractor with a reach up to four meter. The MonoGo is designed for fixed work places and can be mounted to a wall.



DUALGO AND DUALGOPIus

Dual arm fume extractor with a reach up to four meter. All DualGo models have a powerful fan, large filter and are designed to have both extraction arms in operation at the same time.

WHEN TO USE THE GOLINE, GOLINEPIUS AND OTHER PLYMOVENT PRODUCTS

MobileGo and MonoGo are suitable for occasional welding applications	I coil of solid welding wire or 7,5 kg of welding electrodes per month.TIG, due to low fume emission, is unrestricted.			
DualGo and GoLine ^{plus} models are suitable for light and regular welding applications	2 coils of solid welding wire or 15 kg of welding electrodes per month.			
MFD and SFD models are suitable for regular welding	I coil of solid welding wire or 7,5 kg of welding electrodes per week.			
MobilePro, the self cleaning mobile fume extractor is suitable for regular and intensive welding	Fluxed core welding applications, more than I coil of welding wire or 7,5 kg of welding electrodes per week.			
MFS and SFS, the self cleaning fume extractors are suitable for regular and intensive welding	Fluxed core welding applications, more than I coil of welding wire or 7,5 kg of welding electrodes per week.			

^{*} DualGo has same filter as DualGophus



PLYMOVENT GOLINE



"Plymovent GoLine: where protection against welding fume exposure starts."



GOLINE AND GOLINEPAS

The GoLine and GoLine plus of Plymovent is a range of welding fume extractors that provide effective protection against exposure to welding fume at workplaces where welding is less intensive.

The GoLine, is the entry level extractor for occasional welding applications as where the GoLine^{plus} is suitable for more industrial working environments.

WHY THE GOLINE AND GOLINE Plus

- Excellent price performance
- Effective protection against welding fume exposure
- NEN EN ISO 15012-1:2013/W3 compliant
- Suitable for steel and stainless steel welding applications

MOBILEGO AND MOBILEGO Plus

Compact and powerful mobile welding fume extractors fitted with an extraction arm up to three meter length. The arm can rotate 360° degree and is very easy to handle.

MONOGO AND MONOGOPius

Single arm fume extractor with a reach up to four meter. The MonoGo is designed for fixed work places and can be mounted to a wall.



DUALGO AND DUALGOPIUS

Dual arm fume extractor with a reach up to four meter. All DualGo models have a powerful fan, large filter and are designed to have both extraction arms in operation at the same time.

WHEN TO USE THE GOLINE, GOLINEPIUS AND OTHER PLYMOVENT PRODUCTS

MobileGo and MonoGo are suitable for occasional welding applications	I coil of solid welding wire or 7,5 kg of welding electrodes per month.TIG, due to low fume emission, is unrestricted.			
DualGo and GoLine ^{plus} models are suitable for light and regular welding applications	2 coils of solid welding wire or 15 kg of welding electrodes per month.			
MFD and SFD models are suitable for regular welding	I coil of solid welding wire or 7,5 kg of welding electrodes per week.			
MobilePro, the self cleaning mobile fume extractor is suitable for regular and intensive welding	Fluxed core welding applications, more than I coil of welding wire or 7,5 kg of welding electrodes per week.			
MFS and SFS, the self cleaning fume extractors are suitable for regular and intensive welding	Fluxed core welding applications, more than I coil of welding wire or 7,5 kg of welding electrodes per week.			

^{*} DualGo has same filter as DualGo^{bus}



PLYMOVENT GOLINE







MOBILEGO
Perfect for flexible work places.

MONOGO Ideal for fixed work station.

DUALGO
A real space saver!

TECHNICAL SPECIFICATIONS

	MobileGo	MobileGo ^{plus}	MonoGo	Mono Gopks	DualGo	DualGopke
Power	1,1 kW		1,1 kW		2,2 kW	
Voltage	115V-1ph-50Hz 115V-1ph-60Hz 230V-1ph-50Hz		115V-1ph-50Hz 115V-1ph-60Hz 230V-1ph-50Hz		380V-3ph-50Hz 480V-3ph-60Hz 600V-3ph-60Hz	
Sound level	67 dB(A)		67 dB(A)		73 dB(A) Inclusive silencer	
Filter area main filter	15m²	26m²	15m²	26m²	26m²	
Filtration steps	2 steps		2 steps		2 steps	
Efficiency ISO 15012-1	W3		W3		W3	
Service indicator	*		¥.		✓	
Extraction arm ø 160 mm	2 m EA arm 3 m EA arm	2 m KUA arm 3 m KUA arm	2 m EA arm 3 m EA arm 4 m EA arm	2 m KUA arm 3 m KUA arm 4 m KUA arm	2 + 2 m EA arm 2 + 3 m EA arm 2 + 4 m EA arm 3 + 3 m EA arm 3 + 4 m EA arm 4 + 4 m EA arm	2 + 2 m KUA arm 2 + 3 m KUA arm 2 + 4 m KUA arm 3 + 3 m KUA arm 3 + 4 m KUA arm 4 + 4 m KUA arm

EA arm: flexible exterior hose KUA arm: aluminium tube

PLYMIJVENT®

clean air at work

Plymovent cares about the air you breathe. We offer products, systems and services which ensure clean air at work, anywhere in the world.

We respect the environment and we deliver high-quality products. Our expertise gained over many years and our genuine commitment to customer requirements enable us to provide precisely the solutions you need.