


Depth Gauge



Item Code	Description	Measurement Range (mm)	Body Size (mm)	Weight (g)	JAN Code	Packing Unit	Package
19300	Mini	0 - 20	60x55x10	32		10	

Features

- Small size, easy carrying
- Fixing screw

Use

- For measuring groove depth on tires


Specifications

Material	Body: Stainless steel	Screw: Iron
Accuracy	±0.1 mm	

[For Reference] Minimum Tire Groove Depth

Bicycle	0.8 mm
Passenger Car	1.6 mm
Small Truck	1.6 mm
Large Truck	1.6 mm
Bus	1.6 mm

Digital Depth Gauge



Item Code	Description	Measurement Range (mm)	Body Size (mm)	Weight (g)	JAN Code	Packing Unit	Package
19305	Mini 25 mm	0.1 - 25	112.5x60x15	43		10	

Features

- Resin construction makes it lightweight as well as rustproof, and will not scratch other surfaces
- Automatically turns on just by sliding the module
- Auto power off function

Use

- For measuring various depths

Specifications

Material	Body: Nylon resin (with fiberglass)	Digital Module: ABS resin
Accuracy	±0.2 mm	
Minimum Reading	0.1 mm	
Repeatability	0.1 mm	
Use Temperature	0 - 40°C	
Storage Temperature	-10 - 60°C	
Storage Humidity	Below 80%	
Battery	1x Silver oxide battery SR44 <small>(Battery included is for trial use only and may not last as long)</small>	

*Repeatability means the precision earned after repeated measurement.

Digital Depth Gauge with Hold Function



Item Code	Description	Measurement Range (mm)	Body Size (mm)	Weight (g)	JAN Code	Packing Unit	Package
19306	150 mm	0.01 - 150	232x100x15	166		3	
19307	200 mm	0.01 - 200	284x100x15	187		3	

Features

- Ideal for precision work with a minimum reading value of 0.01 mm
- Zero set function enables relative measurement or indirect measurement
- Hold function is useful when the screen cannot be seen
- Automatically turns on just by sliding the module
- Auto power off function



Use

- For measuring depth

Specifications

	19306	19307
Material	Body: Stainless steel	Digital Module: ABS resin
Accuracy	±0.03 mm	
Minimum Reading	0.01 mm	
Repeatability	0.01 mm	
Use Temperature	0 - 40°C	
Storage Temperature	-10 - 60°C	
Storage Humidity	Below 80%	
Battery	1x Silver oxide battery SR44 <small>(Battery included is for trial use only and may not last as long)</small>	

*Repeatability means the precision earned after repeated measurement.