



RC-4 USB Temperature Data Logger RC-4H USB Temperature/R.Humidity Data Logger

1. Product overview:

RC-4/RC-4H USB Temperature & Temperature/R.Humidity Data Logger. LCD display, internal replaceable battery. Has wide monitoring temperature range, high accuracy, large record capacity, etc. The segment LCD could display the current work status, Min/Max & alarm. Has data-processing software with real-time transmission, historical data download, data saving and printing, etc function. RC-4/RC4H is widely used in industries of foodstuff, healthcare, pharmaceutical, cold-chain transportation and other industries compliance with HACCP, GMP, GLP system certification. It could also be used in laboratory where needs temperature and humidity supervision.

2. Product Features:

- Monitor and record temperature/R.Humidity
- Temperature & R.Humidity record interval is user configurable
- Large record capacity. If record every 15 minutes, it could record >3 months.
- Big LCD screen can simultaneously display current work status, Min/Max value.
- Configurable upper/lower temperature alarm limit. It will alarm when the temperature exceeds the upper or lower limit.
- It has USB interface for convenient data download and save in pdf, MS Excel, MS word format
- RC-4/4H come with license free data processing software, download, print and manage the data.



3. Technical Specification:

- Temperature Measuring Range: -30.0°C~60.0 °C (Internal)
-40.0°C~+85.0 °C (External)
- Relative Humidity: 0-100%RH (RC-4H only)
- Temperature accuracy: ± 1.0 °C
- Relative Humidity accuracy: ± 5%
- Display Resolution: 0.1
- Temperature sensor type: NTC
- Record Cycle: 10s to 24 hour continuously set
- Record Capacity: 16,000 points (MAX)
- PC interface: USB interface
- Operation Environment: -30 °C ~ 60 °C; 0% ~ 95%RH
- Standby battery: CR2450 Replaceable battery

Temp. & Humidity Data Logger

Product	: Mini Temp. & Humidity Data Logger
Brand	: Elitech
Model	: RC-4 (T) RC-4H (T & RH)
RC-4 (Temp.)	: - 30°C ~+ 60°C
	- 40°C ~+ 85°C (E / Probe)
RC-4H (Temp.)	: - 30°C ~+ 60°C
	- 40°C ~+ 85°C (E / Probe)
(Humidity)	: 0~99% RH

1) RC-4 Mini Temp. Data Logger
2) RC-4H Mini Temp. & Humidity Data Logger

Hold & Press For 4s. This Symbol Will Light With Indication of Recording

Hold & Press For 4s. This Symbol Will Light With Indication of Stop Recording

4. Standard packing:

- Data logger
- External temperature probe
- Software CD
- USB cable
- Manual

For ordering or more product information please contact,
ExcelTest Monitor & Control (1473869-K)
 Tel : +6 03 78044186
 Fax: +6 03 78046186
 Email: exceltest@excelonez.net Web : www.excelonez.net