


DOT MATRIX PRINTER
9-PIN WIDE CARRIAGE
DFX-9000

EPSON
EXCEED YOUR VISION



**FAST FORWARD YOUR
BUSINESS EFFICIENCY.**

Amplify your productivity with the Epson DFX-9000 dot matrix printer. Featuring speeds of up to 1,550 cps and a MTBF rating of 20,000 power-on hours (POH), this 9-pin, wide format printer can perform high-volume printing with great efficiency and cost-savings. With a convenient LCD panel, versatile connectivity and advanced paper handling capabilities, the DFX-9000 is your reliable choice in a busy environment.



10-copies
Printing High Speed
Printing Power
Saving Cost
Effective



Epson genuine ribbons ensure greater yield, better quality and longer lifespan.

IT'S IN THE DETAILS.

Remarkable Performance

Print speeds of up to 1,550 characters per second (10 cpi) and a user-friendly LCD panel to maximise your productivity.

Efficient and Reliable

Enjoy resilient and long-lasting operations with low cost printing that goes easy on your overheads.

Flexibility and Versatility

Prints up to 10-part forms and offers a wide range of connectivity and paper handling options.

SPECIFICATIONS
9-PIN WIDE CARRIAGE
DFX-9000

Model Number	DFX-9000		
Printer Type	Impact Dot Matrix		
Printing Method	Impact Dot Matrix		
Number of Pins In Head	36 pins (9 × 4 staggered)		
Print Direction	Bi-direction with logic seeking		
Control Code	ESC/P®, IBM® PPDS emulation		
Print Speed			
High Speed Draft	10 / 12 cpi	1,550 / 1,450 cps	
Draft	10 / 12 cpi	1,320 / 1,320 cps	
NLQ	10 / 12 cpi	330 / 330 cps	
Print Characteristics	For Standard version:		
Character Table	Italic table, PC437(US, Standard Europe), PC850(Multilingual), PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), PC861(Icelandic), BRASCLII, Abicomp, Roman 8, ISO Latin 1, PC858, ISO 8859-15		
13 International character sets:			
Bitmap Fonts	EPSON High Speed Draft: 10CPI, 12CPI, EPSON Draft 10CPI, 12CPI, Proportional, EPSON Roman: 10CPI, 12CPI, Proportional, EPSON Sans Serif: 10CPI, 12CPI, Proportional		
Bar Code	EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET		
Printable Columns			
Pitch	10 / 12 / 15 / 17 / 20 cpi	136 / 163 / 204 / 233 / 272 cpi	
Printable Handling	Paper Path	Tractor (Front or Rear in, top out)	
Paper / Media			
Continuous paper		Length	Width
(Single Sheet)		76.2 - 558.8 mm (3.0 - 22.0 inch)	76.2 - 419.1 mm (3.0 - 16.5 inch)
(Multi Part)		76.2 - 558.8 mm (3.0 - 22.0 inch)	76.2 - 419.1 mm (3.0 - 16.5 inch)
		Thickness	0.065 - 0.10 mm (0.0025 - 0.0039 inch)
	Copies	Rear Entry	Front Entry
	Thickness	1 original + 6 copies	1 original + 9 copies
		0.12 - 0.53 mm (0.0047 - 0.021 inch)	0.12 - 0.79 mm (0.0047 - 0.031 inch)
Labels		Base Sheet Length	Base Sheet Width
		76.2 - 558.8 mm (3.0 - 22.0 inch)	76.2 - 419.1 mm (3.0 - 16.5 inch)
			Base Sheet Thickness
			0.07 - 0.09 mm (0.0028 - 0.0035 inch)
			Total Thickness
			0.16 - 0.19 mm (0.0063 - 0.0075 inch)
Continuous forms with labels		Base Sheet Length	Base Sheet Width
		76.2 - 558.8 mm (3.0 - 22.0 inch)	76.2 - 419.1 mm (3.0 - 16.5 inch)
			Total thickness (Rear Entry)
			0.065 - 0.53 mm (0.0025 - 0.021 inch)
			Total Thickness (Front Entry)
			0.065 - 0.79 mm (0.0025 - 0.031 inch)
Overlapping multi-part forms		Base Sheet Length	Base Sheet Width
		76.2 - 558.8 mm (3.0 - 22.0 inch)	76.2 - 419.1 mm (3.0 - 16.5 inch)
			Total thickness (Rear Entry)
			0.13 - 0.53 mm (0.0051 - 0.021 inch)
			Total Thickness (Front Entry)
			0.13 - 0.79 mm (0.0051 - 0.031 inch)
Acoustic Noise	58 dB(A) (ISO7779 pattern)		
Line Spacing	4.23mm(1/6 inch) or programmable in increments of 0.059mm (1/432 inch)		
Input Data Buffer	128 KB		
Interface	Bi-directional parallel interface (IEEE-1284 nibble mode supported), Serial I/F, USB 2.0 (Full Speed) I/F, Optional Serial Interface Board (No Buffer Type-B)		
Ribbon Cartridge	Black		
Colour	Black		
Type	Fabric		
Ribbon life	15 million characters (Draft 10cpi, 14 dots/character)		
Reliability	Mean print volume between failure (MVBFB)		
	133 million lines (except print head)		
MTBF	20,000 POH (25% duty cycle)		
Print head life	200 million strokes/wire		
Control Panel	9 buttons, 6 LEDs and 1 LCD		
Environmental Conditions (operating)	Temperature		
	5 to 35 °C		
	Humidity		
	10 to 80 % RH		
Electrical Specification	Rated Voltage		
	AC 100- 240 V		
	Rated Frequency		
	50-60 Hz		
	Power Consumption		
	Approx. 185 W (ISO/IEC10561 Letter pattern)		
	Approx. 7.5 W in sleep mode		
Printer Driver / Utility	OS		
	Microsoft® Windows® 95/98/2000/Me/XP and Windows® NT® operating system Version 4.0		
	Windows® 7 / 8 (32bit / 64bit) Ultimate / Enterprise / Professional / 10 (32/64bit)		
	Epson Status Monitor ver. 4		
Utility	Microsoft Windows 95/98/Me/NT 4.0/2000		
	Windows XP/7/8/8.1/10 (32/64 bit)		

Dimensions & Weight
Weight: 34kg



Consumables and Options

Ribbon Cartridge (Black)	C13S015505
Pull Tractor unit	C12C800382
Serial Interface Board (No Buffer Type-B)	C12C824432
PS107-iPv6 Network Card	7108323

*1 The recommended average print volume estimate for optimum device performance after factoring supplies replacement intervals and device life.

*2 Complies with ISO-9296.

*3 According to IEC/ISO 19798 yield measurements. Yield may vary depending on printing variables and conditions including toner and page coverage, continuous or intermittent.



© 2019 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Information correct as at March 2019