

DS-D2055NL-E LCD Display



The DS-D2055NL-E LCD display uses an industry-level extreme-narrow bezel design, which enables a bezel width of 1.7 mm between neighboring displays. The adopted direct-lit LED backlighting technology helps achieve ultra-high and uniform brightness of 500 cd/m² without boundary shadows. The display has abundant interfaces for video inputs, such as DVI, VGA, and HDMI.


- Direct-lit LED backlight with uniform brightness and no boundary shadows
- 1920 × 1080 resolution, 178° viewing angle
- Extreme narrow 1.7 mm bezel design
- Factory calibration for color uniformity
- Anti-glare, high definition, high brightness, high color gamut, and vivid images with rich colors
- Stable and 24-hour continuous working
- Metal casing for preventing from radiation and magnetic & electric field interference
- Wall-mount and modular brackets available to meet various installation requirements



▪ Specification

Model		DS-D2055NL-E
Product Model	Product Model	DS-D2055NL-E
Display	Screen Size	55 inch
	Active Display Area	1209.6 (H) mm × 680.4 (V) mm
	Backlight	Direct-lit LED backlight
	Pixel Pitch	0.63 mm
	Physical Seam	1.7 mm
	Bezel Width	1.1 mm (top/left), 0.6 mm (bottom/right)
	Resolution	1920 × 1080@60 Hz (downward compatible)
	Brightness	500 cd/m ²
	Viewing Angle	Horizontal 178°, vertical 178°
	Color Depth	8 bit, 16.7 M
	Contrast Ratio	4000:1
	Response Time	8 ms (G to G)
	Color Gamut	72% NTSC
	Surface Treatment	Haze 25%, 2H
Interface	Video & Audio Input	HDMI × 1, DVI × 1, VGA × 1, CVBS × 1, USB × 1
	Video & Audio Output	DVI × 1, VGA × 1, CVBS × 1
	Control Interface	RS232 IN × 1, RS232 OUT × 1
Power	Power Supply	100-240 VAC, 50/60 Hz
	Power Consumption	≤ 192 W
	Standby Consumption	≤ 0.5 W
Working Environment	Working Temperature	0°C to 40°C (32°F to 104°F)
	Working Humidity	20% to 90% RH (non-condensing)
	Storage Temperature	-20°C to 65°C (-4°F to 149°F)
	Storage Humidity	5% to 90% RH (non-condensing)
General	Casing Material	SECC
	VESA	600 (H) mm × 400 (V) mm
	Product Dimension (W × H × D)	1211.54 mm × 682.34 mm × 69.5 mm (47.7" × 26.86" × 2.74")
	Package Dimension (W × H × D)	Carton with two displays: 1404 mm × 910 mm × 464 mm (55.28" × 35.83" × 18.27") Carton with a single display: 1404 mm × 910 mm × 464 mm (55.28" × 35.83" × 18.27")
	Net Weight	24.28 ± 0.5 Kg (53.53 ± 1.1 lb) for single display
	Gross Weight	62.86 ± 0.5 Kg (138.58 ± 1.1 lb) for carton with two displays 36.21 ± 0.5 Kg (79.83 ± 1.1 lb) for carton with a single display
	Packing List	LCD display × 1, power cable × 1, network cable × 1, screw × 4, installation instruction × 1, remote control × 1, IR receiver × 1, CD-ROM × 1, RS-232 converter × 1


▪ Physical Interface



Interface	Description	Interface	Description
POWER	Power indicator	HDMI IN	HDMI input interface
DVI OUT	DVI-I output interface for digital signals	DVI IN	DVI-I input interface for digital signals
VGA OUT	VGA output interface for analog signals	VGA IN	VGA input interface for analog signals
CVBS OUT	CVBS output interface for signals	CVBS IN	CVBS input interface for signals

USB	USB interface	RS232 IN	Serial loopback input interface
RS232 OUT	Serial loopback output interface	IR IN	IR input interface

Dimension



Available Model

DS-D2055NL-E

Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com