

iCAM7000 Advanced Multifactor Biometric IRIS Reader

The **iCAM7000** series scanner allows rapid iris acquisition with great image quality for superior enrolment and recognition, made possible with its intuitive and interactive interface.

This biometric iris solution is highly versatile and flexible, and provides highly accurate, non-contact identification with each individual's unique iris characteristics.


Recommended applications include Transportation & Immigration, Public Safety & Justice, National Identity, and Access Control & Time Attendance.






Key Features

- Fast & Fully Automatic Dual Iris Capture
- Non-intrusive, Non-contact User Interface
- 1:N and 1:1 Matching
- Integrated Contactless Smartcard Reader
- ISO 19794-6 Compliance
- Touch Screen LCD and PIN Pad (iCAM7100)
- Auto Tilt with use of Smartcard or PIN
- Audio and Visual Prompts
- Hygienic and Clean
- Easy to Install and Maintain
- Convenient Remote Management
- Flush or recess mounting

Product Guide




Easy to Use User Interface



- iCAM activates when user approaches or when card is presented
- Picture capture range of 30~35cm (12"~14") away
- Self/Auto set height adjustment
- Dot on the bridge of nose to facilitate alignment
- Orange dot turns to green when user is at correct distance
- Friendly audio prompts supplement visual indication
- Right and Left irides are acquired automatically

Schematic Diagram



Technical Specifications

Specifications*	iCAM7000S-B
Description	Advanced Multifactor Biometric Iris Reader
User Input	6x Function Keys (User Definable)
Voice Indication	English, others by download
Iris Capture Range	31 - 35 cm (12" - 14")
Iris Camera Rotation Angle	+35°/ -25°
Iris Operating Range Indicator	Dual Color-Orange (out of range), Green (in range)
Status LED	Multi Color-Red, green, Blue for status indication
Touch Screen LCD Display	480 x 272 pixels (4.3") (iCAM7100)
PIN Pad	Pop-up on Screen (iCAM7100)
Communications	Ethernet (LAN, WAN), RS422 (output only),
Communications	RS232 (input only from external card readers)
Transaction Log Capacity	Up to 100,000 FIFO transactions stored on device, unlimited on server
Inputs/ Outputs	Proximity Card Reader (Wiegand In), Embedded Smart Card Reader (Optional), Wiegand In, Wiegand Out, 2x Dry Contact Relays, 4x Programmable GPIO
Power Input/ Consumption	12 - 24 VDC, 2.0 A @ 12 VDC, 24 W
Dimensions (H x W x D)	211 x 178 x 64 mm
Weight	1500 g
Operating Temperature/ Humidity	0°C to 45°C/ up to 90% non-condensing

*Specifications are subject to change without prior notice

Ordering Information

Model No.	Description
iCAM7000S-B	Dual Iris Recognition Camera
iCAM7101S-B	Dual Iris Recognition Camera w/Keypad & LCD
iCAM7111S-H1B	Dual Iris Recognition Camera & Reader w/Keypad & LCD
iCAM7-RMB	Recess Mount Kit for iCAM 7 series
iCAM7-PWR	Power Supply for iCAM 7 series
EAC500	Multifactor Biometric Iris Scan Reader for up to 500 Users
EAC2500	Multifactor Biometric Iris Scan Reader for up to 2,500 Users
EAC5000	Multifactor Biometric Iris Scan Reader for up to 5,000 Users
EAC10K	Multifactor Biometric Iris Scan Reader for up to 10,000 Users

* For more than 30,000 users, please contact our Sales team