



Features

- Force, distance and time measurement for time-synchronous measurement data acquisition (sensor optional)
- Comprehensive test analysis software package for recording and extensive evaluation of test results
- Target-actual comparisons of force-displacement curves with freely definable good / bad ratings
- Application as force sensor in test stands » with rugged aluminium die cast housing, optimized fixing points and autoreverse display

Technical data

		Order No.:								
		FMI-S50A5	FMI-S50B1	FMI-S50B5	FMI-S50C1	FMI-S50C2	FMI-S50C5	FMI-S50K1	FMI-S50K2	FMI-S50K5
Capacity F(nom)*	N	5	10	50	100	250	500	1000	2500	5000
Resolution**	N	0,001	0,002	0,01	0,02	0,05	0,1	0,2	0,5	1
Tolerance**	% F(nom)	0,15								
Temperature coefficient*	% / K	0,02								
Reproducibility*	% F	0,03								
Repeatability*	% F	0,03								
Hysteresis*	% F	0,075								
Creeping (5min)*	% F	0,15								
Measurement error**	% F(nom)	0,3								
Measuring principle		Bidirektionaler Kraftsensor mit Dehnungsmessstreifen und High-Speed ?-Prozessor								
Nominal deflection*	mm	0,17	0,34	0,13	0,25	0,23	0,17	0,34	0,13	0,26
Measuring shaft		M6							M10	

Version: 19.11.2019

All data are valid at the time of generating this document. Technical changes or any other changes of the product may become effective at any time and without prior notice. All pictures and drawings are reference only. © Alluris GmbH & Co. KG, Alluris® is a registered trade mark of Alluris GmbH & Co. KG.

Alluris GmbH & Co. KG | Basler Straße 65 | 79100 Freiburg | Germany

Tel: 0761 47979 3 | e-mail: info@alluris.de

www.alluris.de/en

Max. operating force*	% F(nom)	120	
Breaking force*	% F(nom)	500	200
Display	Type	5-digit LCD 12mm Autoreverse	
	Refresh time (ms)	10 ... 1000	
Operation modes	Regular	N kg lb	
	Peak (real-time)	Display of peak value Peak value of pull- or push force (drag indicator function)	
	Limits + Statistik	2 separately adjustable limits Single value memory and continuous measured value memory	
Power supply	Type	Solar cell USB (max. 900 mA)	
	Connection	USB (socket)	
Temperature (operation)*	°C	0 ... 40	
Protection code (EN 60529)	Cable not plugged	IP40	IP65
Housing	Material	Aluminium die cast	Hardened steel
	LxWxH (mm)	150 x 82 x 29	
	Weight (kg)	0,480	1,150
	Mounting	2xM4, 2xM5, adjusting holes D5(H7)	

*) according VDI/VDE/DKD 2638 at 0,2 ...1 x F(nom) **) according DIN 1319-1

Scope of Supply

Force gauge with force introduction parts (hook, flat head, groove head, pressure cone), USB cable, Quickstart manual, transport and protective case. Including FMI_Analyze software for real-time data acquisition Force/Distance/Time. Including calibration protocol according to VDI/VDE 2624 sheet 2.1 (DAkkS accredited calibration laboratory).

Version: 19.11.2019

All data are valid at the time of generating this document. Technical changes or any other changes of the product may become effective at any time and without prior notice. All pictures and drawings are reference only. © Alluris GmbH & Co. KG, Alluris® is a registered trade mark of Alluris GmbH & Co. KG.

Alluris GmbH & Co. KG | Basler Straße 65 | 79100 Freiburg | Germany

Tel: 0761 47979 3 | e-mail: info@alluris.de

www.alluris.de/en