



Features

- Data logging and USB interface » with memory function and limit value monitoring
- Peak measurement with 0,15 % accuracy » a high measurement rate allows to detect tensile and break forces precisely
- Application as force sensor in test stands » with rugged aluminium die cast housing, optimized fixing points and autoreverse display

Technical data

		Order No.:								
		FMI-S30A5	FMI-S30B1	FMI-S30B5	FMI-S30C1	FMI-S30C2	FMI-S30C5	FMI-S30K1	FMI-S30K2	FMI-S30K5
Capacity F(nom)*	N	5	10	50	100	250	500	1000	2500	5000
Resolution**	N	0,001	0,002	0,01	0,02	0,05	0,1	0,2	0,5	1
Tolerance**	% F(nom)	0,15								
Temperature coefficient*	% / K	0,02								
Repeatability*	% F	0,03								
Creeping (5min)*	% F	0,15								
Measurement error**	% F(nom)	0,3								
Measuring principle		Bidirectional force sensor with strain gauges and high-speed ?-processor								
Nominal deflection*	mm	0,17	0,34	0,13	0,25	0,23	0,17	0,34	0,13	0,26
Measuring shaft		M6						M10		
Max. operating force*	% F(nom)	120								
Breaking force*	% F(nom)	500						200		

Version: 19.11.2019

All data are valid at the time of generating this document. Technical changes or any other changes of the product may become effective at any time and without prior notice. All pictures and drawings are reference only. © Alluris GmbH & Co. KG, Alluris® is a registered trade mark of Alluris GmbH & Co. KG.

Alluris GmbH & Co. KG | Basler Straße 65 | 79100 Freiburg | Germany

Tel: 0761 47979 3 | e-mail: info@alluris.de

www.alluris.de/en

Display	Type	5-digit 12mm Autoreverse	
	Refresh time (ms)	10 ... 1000	
Operation modes	Regular	N kg lb	
	Peak (real-time)	Display of peak value Peak value of pull- or push force (drag indicator function)	
	Limits + Statistik	2 separately adjustable limits Single value memory and continuous measured value memory	
Power supply	Type	Solar cell USB (max. 900 mA)	
	Connection	USB (socket)	
Temperature (operation)*	°C	0 ... 40	
Protection code (EN 60529)	Cable not plugged	IP40	IP65
Housing	Material	Aluminium die cast	Hardened steel
	LxWxH (mm)	150 x 82 x 29	
	Weight (kg)	0,480	1,150
	Mounting	2xM4, 2xM5, adjusting holes D5(H7)	

*) according VDI/VDE/DKD 2638 at 0,2 ... 1 x F(nom) **) according DIN 1319-1

Scope of Supply

Force gauge with force introduction parts (hook, flat head, groove head, pressure cone), Quickstart manual, transport and protective case. Free software for MsExcel data transfer to download.

Version: 19.11.2019

All data are valid at the time of generating this document. Technical changes or any other changes of the product may become effective at any time and without prior notice. All pictures and drawings are reference only. © Alluris GmbH & Co. KG, Alluris® is a registered trade mark of Alluris GmbH & Co. KG.

Alluris GmbH & Co. KG | Basler Straße 65 | 79100 Freiburg | Germany

Tel: 0761 47979 3 | e-mail: info@alluris.de

www.alluris.de/en