



Features

- Operators panel with full color bright 10,4" TFT touchpanel.
- Rigid linear guide with precision ball screw, designed for 5 kN.
- Manual operation modes and predefined test runs, expandable at any time via internet portal.
- Real time display with force vs. length diagramm, data transfer and filing with standard webbrowser.

Technical data

		Order No.:							
		FMT-314.06A5	FMT-314.06B5	FMT-314.06C5	FMT-314.06K5	FMT-314.12A5	FMT-314.12B5	FMT-314.12C5	FMT-314.12K5
Speed	mm/min	1200							
Connection / Tool holder	Gewinde	M4 / M10	M6 / M10		M10 / M10	M4 / M10	M6 / M10		M10 / M10
Current consumption	A @ 230 V AC	3,8							
Control panel	Type	10,4" Color TFT / Touch PCAP							
Ethernet (socket)	Type	100Base-TX (RJ45)							

Scope of Supply

Version: 29.05.2019

All data are valid at the time of generating this document. Technical changes or any other changes of the product may become effective at any time and without prior notice. All pictures and drawings are reference only. © Alluris GmbH & Co. KG, Alluris® is a registered trade mark of Alluris GmbH & Co. KG.

Alluris GmbH & Co. KG | Basler Straße 65 | 79100 Freiburg | Germany

Tel: 0761 47979 3 | e-mail: info@alluris.de

www.alluris.de/en