



**AS**

**PHTPW**

# **POW'RENCH Manual Impact Wrench**

**Available in 1/2, 3/4, and 1" Drive**

**POW'RENCH Manual Impact Wrench is the Faster, Easier and Safer Alternative to the Breaker Bar**

## **Features and Benefits**

- Operates without hydraulics, compressed air or other power sources
- Roto-Sledge™ Power Impact Head Technology converts spring energy into powerful torsional blows
- Delivers impact of up to 63 times the force applied to the handle
- Lightweight and portable; operates wherever needed, including under water
- Replaces burning, hacking and chiseling; saves man-hours, machine time and downtime
- Minimizes the need for operator strength and skill
- Provides a safer fastener-removal solution—replaces breaker bars that can fall with the sudden release of a frozen fastener
- Prevents impact “shock” transmission through the handle to the operator
- For use with impact sockets with high torque tolerances
- Available in 500, 800 and 2,000 ft-lb ratings



**PHTPW50050**

CE - Not Required

Country of Origin: USA

**Snap-on**

**September 2021  
Page 1 of 2**



AS

## Applications

- Heavy Duty
- Municipal
- Fleet Maintenance
- Emergency Road Crews
- Breaker Bar Alternative
- Space constraints
- Power or pneumatic are unavailable

PHTPW2000100

PHTPW80075

PHTPW50050



## Specifications

Stock No.	Square Drive, inches	Style	Max Torque Output, ft-lb	A	B	C	Max Pull on Handles, in-lb	Weight, lb (kg)
PHTPW50050	1/2	Bi-Directional	500	1-5/8	12	1-21/32	39*	6 (2.7)
PHTPW50075	3/4	Bi-Directional	500	1-5/8	12	1-21/32	39*	6 (2.7)
PHTPW80075	3/4	Bi-Directional	800	2	16	2	50*	11 (4.9)
PHTPW2000100	1	Bi-Directional	2,000	2-1/2	24	2-5/8	75*	23 (10.4)

\*Max pull of the handle, in lbs., to deliver torque output

### WARNING



Impact Sockets - Sockets designed for durability when used with impact drivers, use only impact sockets with impact drivers



Wear safety goggles (User and Bystander)  
Read additional safety warnings on pages W1 to W4 in Catalog 1500

Snap-on

September 2021  
Page 2 of 2