

# HEAVY-DUTY CARTS



**Modular system:**

Multi-functional modular system with the proven fetra „Insert & Bolt Principle“. The Super MultiVario transport carts can be changed, swapped and added-on in many ways.

**Platform:**

Anti-skid waterproof plywood board.



**Elastic solid rubber tyres:**

Very comfortable due to easy, highly elastic running. Non-marking, hubs with ball bearings.

**Sturdy and elegant:**

Specially designed for heavy loads. Optical of one cast with round edges.



Super-MultiVario transport cart **12503**



**Super-MultiVario-Transporter**

**Modular System**

The Super-MultiVario-transporter is especially designed for heavy loads.

High-quality elasticated solid-rubber wheels and hubs with ball bearings guarantee an extreme manoeuvrability and a smooth run.

Steel tube and sectional steel welded, powder coated, blue RAL 5007. Platforms and ends made of antislip waterproof plywood boards (insert type of board).

2 swivel and 2 fixed-wheel castors, elasticated solid rubber tyres 200 x 50 mm, blue-grey „trackless“, hubs with ball bearings.

Swivel castors with wheel locks.

Usable height 283 mm.

**Stanchioned trolleys 12582 - 12586**

With 4 insertable stanchions.

Usable height 600 mm.

**Accessories**  
on pages 183-185



12592 | 12593 | 12595 | 12596



12582 | 12583 | 12585 | 12586



12502 | 12503 | 12505 | 12506

	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Outside dimensions L x W x H mm	Net weight kg
Platform trolleys	12592	1200	200	1000 x 700	1076 x 700 x 283	38
	12593	1200	200	1200 x 800	1276 x 800 x 283	42
	12595	1200	200	1600 x 800	1676 x 800 x 283	56
	12596	1200	200	2000 x 800	2076 x 800 x 283	86
Stanchioned trolleys	12582	1200	200	1000 x 700	1076 x 700 x 887	42
	12583	1200	200	1200 x 800	1276 x 800 x 887	46
	12585	1200	200	1600 x 800	1676 x 800 x 887	60
	12586	1200	200	2000 x 800	2076 x 800 x 887	90
Open carts	12502	1200	200	1000 x 700	1155 x 700 x 1005	42
	12503	1200	200	1200 x 800	1355 x 800 x 1005	47
	12505	1200	200	1600 x 800	1755 x 800 x 1005	60
	12506	1200	200	2000 x 800	2155 x 800 x 1005	87





**Super-MultiVario-Transporter Modular System**

The Super-MultiVario-transporter is especially designed for heavy loads.

High-quality elasticated solid-rubber wheels and hubs with ball bearings guarantee an extreme manoeuvrability and a smooth run.

Steel tube and sectional steel welded, powder coated, blue RAL 5007. Platforms and ends made of antislip waterproof plywood boards (insert type of board).

2 swivel and 2 fixed-wheel castors, elasticated solid rubber tyres 200 x 50, blue-grey „track-less“ hubs with ball bearings. Swivel castors with wheel locks.



12512 | 12513 | 12515 | 12516



12497

**Panelled end platform carts 12512 - 12516**

Side panels made of antislip waterproof. Side panel height: 500 mm



12402 | 12403 | 12405 | 12406



12422 | 12423 | 12425 | 12426

**Table top cart 12497**

Square platforms. Capacity upper platform 500 kg.

**Table top cart 12402 - 12406 12422 - 12426**

Rectangular platforms. Capacity upper and middle platform 500 kg.



**Add-on kit for table top carts**  
steel plate drawer with ball pull-out and cylinder lock.  
Height x Width x Depth inside 105 x 410 x 475 mm.



**Drawer subdivision-set**  
made of galvanized steel sheet, insertable. 2 longitudinal partitions and 6 dividing sheets.

**Add-on kit 2149**

Steel plate drawer with ball pull-out and cylinder lock. Height x Width x Depth inside 105 x 410 x 475 mm (2 kits per cart possible, for type 12497 1 kit per cart).

	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Outside dimensions L x W x H mm	Shelf heights mm	Net weight kg
<b>Panelled end platform carts</b>	12512	1200	200	1000 x 700	1155 x 700 x 1005	283	45
	12513	1200	200	1200 x 800	1355 x 800 x 1005	283	52
	12515	1200	200	1600 x 800	1755 x 800 x 1005	283	64
	12516	1200	200	2000 x 800	2155 x 800 x 1005	283	96
<b>Table top carts</b>	12497	1200	200	700 x 700	910 x 700 x 925	283, 925	54
	12402	1200	200	1000 x 700	1210 x 700 x 925	283, 925	67
	12403	1200	200	1200 x 800	1410 x 800 x 925	283, 925	77
	12405	1200	200	1600 x 800	1810 x 800 x 925	283, 925	100
	12406	1200	200	2000 x 800	2210 x 800 x 925	283, 925	156
	12422	1200	200	1000 x 700	1210 x 700 x 925	283, 604, 925	97
	12423	1200	200	1200 x 800	1410 x 800 x 925	283, 604, 925	108
	12425	1200	200	1600 x 800	1810 x 800 x 925	283, 604, 925	144
12426	1200	200	2000 x 800	2210 x 800 x 925	283, 604, 925	228	
<b>Sheet steel drawer</b>	2149	-	-	-	-	-	-
<b>Subdivision-set</b>	2148/ES	-	-	-	-	-	-

**Accessories on pages 183-185**



## Super-MultiVario-Transporter Modular System

The Super-MultiVario-transporter is especially designed for heavy loads. Steel tube and sectional steel welded, powder coated, blue RAL 5007.

1 fix and 3 shelves made of waterproof stable plywood boards. 1 side anti-slip the other side smooth.

Variable use of shelves, minimum distance 100 mm.

Shelf heights:  
283, 688, 1088, 1488 mm

Capacity per shelf 180 kg.

High-quality elasticated solid-rubber wheels and hubs with ball bearings guarantee an extreme manoeuvrability and a smooth run.

2 swivel and 2 fixed-wheel castors, elasticated solid rubber tyres 200 x 50, blue-grey „trackless“ hubs with ball bearings.

Swivel castors with wheel locks.

### Shelved trolleys

18212 -1 | 18213-1  
18312 -1 | 18313-1

Ends of tubular construction with intermediate uprights at intervals of approx. 130 mm. Detachable side panels, also with intermediate uprights.

### Shelves

Additional charge or price reduction for shelves including 1 pair of support brackets.

Size mm	Order no.
1000 x 700	E18202ETAW
1200 x 800	E18203ETAW

Accessories  
on pages 183-185



18202 | 18203



18212-1 | 18213-1



18302 | 18303



18312-1 | 18313-1

	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Outside dimensions L x W x H mm	Net weight kg
Shelved trolleys	18202	1200	200	1000 x 700	1173 x 700 x 1583	85
	18203	1200	200	1200 x 800	1373 x 800 x 1583	101
	18212-1	1200	200	1000 x 700	1184 x 724 x 1583	103
	18213-1	1200	200	1200 x 800	1384 x 824 x 1583	121
	18302	1200	200	1000 x 700	1173 x 700 x 1817	84
	18303	1200	200	1200 x 800	1373 x 800 x 1817	103
	18312-1	1200	200	1000 x 700	1184 x 724 x 1817	110
	18313-1	1200	200	1200 x 800	1384 x 824 x 1817	128



# TROLLEYS WITH CARRIER SPARS

**Robust construction:**

Strong frame made of square tube bolted together with sturdy brackets.

**Variable system:**

Carrier spars adjustable, either on one or both sides. Can be customised as needed with additional components.



**TPE castor:**

The innovative easy-running TPE-castor in the attractive fetra design is non-marking and odourless. Particularly smooth-running groove ball bearing.



**Wooden shelves:**

Made of water-resistant plywood with anti-skid and smooth side.

Trolley with carrier spars **4615-1AS**



4614 | 4615 | 4616



4624 | 4625 | 4626



Trolley with carrier spars with PVC hose



Anti-skidding device



Push handle

**Trolleys with carrier spars**

**Modular system**

A very versatile system for transport and storage of long goods. Carrier spars steplessly adjustable. Trolley completely bolted.

Frame made of sturdy square tube. Cross beams, posts and bars connected with solid screwed joints. Carrier spars made of tubular steel Ø 27 mm with screwed joints. Powder coated blue RAL 5007.

2 swivel and 2 fixed-wheel castors, TPE tyres, hubs with groove ball bearing. Swivel castors with wheel locks.

Flat packed delivery.

**4614 | 4615 | 4616**

12 one-side carrier spars, useful length 600 mm, useful height of stand 1450 mm.

Carrying capacity per level 80 kg.

**4624 | 4625 | 4626**

24 carrier spars on both sides (12 per side), useful length 370 mm, useful height of stand 1450 mm.

Carrying capacity per level 120 kg (60 kg per side).

**Special version: PVC hose**

Carrier spars covered with PVC hose, 3 mm thick, as anti-skid protection. Facilitates the careful handling of the goods.

**Anti-skidding device**

Insertable as a stopper at the end of the carrier spar.

Useful height: 30 mm

Useful height of PVC hose: 27 mm

Additional charge per trolley with

- one-side carrier spars
- carrier spars on both sides

Additional charge anti-skidding device for single carrier spar

Add „AS“ to order no. of the trolleys or carrier spar, e.g., 4614AS“ or „E4614TAAS“.

**Push handle**

can be bolted onto the outer post of the trolley by means of clamping brackets.

Order no. 4680

**Accessories**

on pages 110, 183-185

	Capacity kg	Frame L x W mm	TPE tyres mm	Outside dimensions L x W x H mm	Trolley with carrier spars powder coated		Trolley with carrier spars powder coated with PVC hose	
					Order no.		Order no.	
Trolleys with carrier spars	500	1200 x 800	200 x 40	1400 x 800 x 1807	4614		4614-1	
	500	1600 x 800	200 x 40	1800 x 800 x 1807	4615		4615-1	
	500	2000 x 800	200 x 40	2200 x 800 x 1807	4616		4616-1	
	500	1200 x 800	200 x 40	1400 x 800 x 1807	4624		4624-1	
	500	1600 x 800	200 x 40	1800 x 800 x 1807	4625		4625-1	
	500	2000 x 800	200 x 40	2200 x 800 x 1807	4626		4626-1	





**Modules for trolleys with carrier spars**

Trolleys can be completed with these modules as often as required, e.g. with further posts and carrier spars or cross beams.

**Shelves for trolleys with carrier spars**

Platform of waterproof plywood 15 mm thick, usable on both sides, one side is smooth, the other side an anti-slip surface (plywood), with fastening clamps.

**Carrier spars for trolleys with carrier spars 600 mm long**

Not suitable for double-sided mounting.



Modules for trolleys with carrier spars



Shelves for trolleys with carrier spars

		Order no.
Modules for trolleys with carrier spars	1	Horizontal bar 1200 mm long
		Horizontal bar 1600 mm long
		Horizontal bar 2000 mm long
	2	External post
	3	Middle post
	4	Cross beam (without rolls)
5	Carrier spar 370 mm long (1 set = 2 pieces)	E4624TA
	Carrier spar 370 mm long with PVC-hose (1 set = 2 pieces)	E4624-1TA
6	Carrier spar 600 mm long	E4614TA
	Carrier spar 600 mm long with PVC-hose	E4614-1TA

		For carrier spars without PVC hose		For carrier spars with PVC hose	
Size		Order no.		Order no.	
Shelves for trolleys with carrier spars	7	1200 x 600 mm	E4614ET	E4614-1ET	
		1600 x 600 mm	E4615ET	E4615-1ET	
		2000 x 600 mm	E4616ET	E4616-1ET	
8	1200 x 370 mm	E4624ET	E4624-1ET		
	1600 x 370 mm	E4625ET	E4625-1ET		
	2000 x 370 mm	E4626ET	E4626-1ET		

# WORK PIECE TROLLEYS

**Tidiness at the assembling place:**  
Individual configuration with carriers, boxes and trays.

**Extrem robust:**  
Stable angle steel construction, with wire lattice inwelded, mesh width 75 x 75 mm, wire thickness 7 mm!



**TPE castor:**  
The innovative easy-running TPE-castor in the attractive fetra design is non-marking and odourless. Particularly smooth-running groove ball bearing.



**Continuous loading platform:**  
Also in the centre for transporting long goods.

Work piece trolley 1301 + accessories



**1301**

Workpiece trolley, in sectional steel, with welded wire lattice 75 x 75 mm, powder coated, blue RAL 5007. Continuous platform of derived timber material board, surface beech grain.

2 swivel and 2 fixed-wheel castors, TPE tyres, hubs with precision deep groove ball bearing. Swivel castors with wheel locks, according to the European Standard EN 1757-3 (safety of platform trolleys).

Height of superstructure 1250 mm  
Total height 1536 mm  
Wire lattice frame inclined at 11%.



1301 with accessories

**Accessories:**

Steel welded, powder coated, grey RAL 7035

**Thorn bracket**

10 mm Ø, Length 200 and 300 mm, Capacity 10 kg

**Tubular bracket**

16 mm Ø, Length 300 mm, Capacity 15 kg  
22 mm Ø, Length 300 mm, Capacity 15 kg  
27 mm Ø, Length 300 mm, Capacity 25 kg

**Corrugated bracket**

Corrugation spacing, 55 mm, Length 320 mm, Capacity 25 kg

**Forked bracket**

Clearance 50 mm, Length 300 mm, Capacity 25 kg

**Material box**

L x W x H, 250 x 150 x 80 mm  
Capacity 25 kg

**Material tub**

L x W x H = 1200 x 250 x 40 mm  
Capacity 50 kg

**Storage box, open**

Polypropylene blue, L x W x H 300 x 230 x 150 mm

**Accessories**

on pages 183-185



Thorn bracket 1310



Tubular bracket 1312



Material box 1306



Tubular bracket 1302



Tubular bracket 1303



Material tub 1316



Corrugated bracket 1314



Forket bracket 1305



Storage box 1307

	Order no.	Capacity kg	Platform size L x W mm	TPE tyres mm	Net weight kg
<b>Workpiece trolleys</b>	1301	600	1200 x 800	200 x 40	90

	Order no.	Capacity kg	Size mm	Net weight kg
<b>Thorn bracket</b>	1310	10	10 Ø x 200 length	0,3
	1311	10	10 Ø x 300 length	0,4
<b>Tubular bracket</b>	1312	15	16 Ø x 300 length	0,3
	1302	25	22 Ø x 300 length	0,4
	1303	25	27 Ø x 300 length	0,5
<b>Corrugated bracket</b>	1314	25	320 length	0,6
<b>Forket bracket</b>	1305	25	50 mm clearance x 300 mm length	1,0
<b>Material box</b>	1306	25	L x W x H = 250 x 150 x 80	1,1
<b>Material tub</b>	1316	50	L x W x H = 1200 x 250 x 40	7,0
<b>Storage box, open</b>	1307		L x W x H = 300 x 230 x 150	0,5

# SHEET MATERIAL TRANSPORT

**Perfect fit:**

7 adjustment positions for insertable tubular supports, perfectly integrated into the frame design.

**Various possibilities for applications:**

For transporting and storing large panels.



**TPE castor:**

The innovative easy-running TPE-castor in the attractive fetra design is non-marking and odourless. Particularly smooth-running groove ball bearing.



**Robust:**

Standard capacity 750 kg, optional 1200 kg.

Trolley for sheet material **4463 + accessories**





**Dollies for sheet material  
4155 | 4156**

Dolly for sheet material with clamping jaws. Steel-welded construction, powder coated blue RAL 5007.

Jaw surface with felt coating. Wheels with either solid rubber or pneumatic tyres, hubs with roller bearings.

Secure clamping by the weight of the load on the clamping construction. Maximal clamping width: 0-60 mm



4155 | 4156



4157 | 4158

**4157 | 4158**

As 4155 | 4156, but clamping width 30-95 mm (suitable for windows).

**Dollies for sheet material  
4165 | 4166**

Dolly for sheet material in U-form. Steel sheet construction, powder coated blue RAL 5007, interior surface with felt coating.

Wheels with either solid rubber or pneumatic tyres, hubs with roller bearings.

Clear width: 150 mm



4165 | 4166



4175 | 4176

**4175 | 4176**

Dolly for sheet material as 4165 | 4166, but with support and push bar.

Clear width: 150 mm



Example of use

	Order no.	Capacity kg	Height mm	Lifting blade length mm	Lifting blade width mm	Total width mm	Solid rubber tyres mm	Pneumatic tyres mm	Net weight kg
Dollies for sheet material	4155	250	305	300	60	284	260 x 56	-	8
	4156	250	305	300	60	298	-	260 x 85	6
	4157	250	307	300	95	319	260 x 56	-	8
	4158	250	307	300	95	333	-	260 x 85	6
	4165	500	260	500	150	343	260 x 56	-	8
	4166	400	260	500	150	357	-	260 x 85	6
	4175	500	905	500	150	343	260 x 56	-	10
	4176	400	905	500	150	357	-	260 x 85	8



1075 | 1076



2075 | 2076

**Carts for sheet material  
1075 | 1076**

Carts for longitudinal transport of bulky wooden boards and plastic sheets. Tubular steel construction with steel sheet blade, powder coated blue RAL 5007.

Wheels with either solid rubber or pneumatic tyres. Hubs with roller bearings.

2 support wheels 50 mm Ø.  
Flat packed delivery.

**2075 | 2076**

Cart for sheet material as 1075 | 1076 but fitted with rubber strip (nonskid).  
With holding-down clamp as tilt lock.



Example of use

	Order no.	Capacity kg	Height mm	Lifting blade length mm	Lifting blade width mm	Total width mm	Solid rubber tyres mm	Pneumatic tyres mm	Net weight kg
Carts for sheet material	1075	400	1430	500	200	680	250 x 60	-	18
	1076	350	1440	500	200	680	-	260 x 85	16
	2075	400	1450	500	200	680	250 x 60	-	20
	2076	350	1460	500	200	680	-	260 x 85	18





**Trolleys for sheet material**

4411 | 4412 | 4413

With fixed tubular supports. Tubular steel and profile steel welded, powder coated blue RAL 5007. Platform made of derived timber material board, surface beech grain. Bolted tubular steel superstructure. 2 swivel and 2 fixed-wheel castors, TPE tyres, hubs with groove ball bearing. Swivel castors with wheel locks.

Effective height: 1050 mm  
Height retaining bracket: 300 mm

4431 | 4432 | 4433

as 4411 | 4412 | 4413, but platform with glued-on fine rubber. Slip-resistant. Saves sensitive transport goods.

4445

Welded profile steel and steel tube. Anti-skid loading platform of waterproof plywood.

2 swivel and 2 fixed-wheel castors, TPE tyres, hubs with groove ball bearing. Swivel castors with wheel locks.

Effective height: 1150 mm



4411 | 4412 | 4413



4431 | 4432 | 4433



4445

	Order no.	Capacity kg	Wheel-Ø mm	Platform size LxW mm	Outside dimensions LxWxH mm	Net weight kg
Trolleys for sheet material	4411	600	200	1070 x 335	1070 x 610 x 1321	36
	4412	600	200	1070 x 435	1070 x 710 x 1321	41
	4413	600	200	1270 x 535	1270 x 810 x 1321	45
Trolleys for sheet material	4431	600	200	1070 x 335	1070 x 610 x 1321	34
	4432	600	200	1070 x 435	1070 x 710 x 1321	39
	4433	600	200	1270 x 535	1270 x 810 x 1321	43
Trolleys for sheet material	4445	500	200	1500 x 400	1500 x 710 x 1510	59



Pallet feet 2021



Trolleys for sheet material

4463 | 4463-1  
4465 | 4465-1

Up to 1200 kg capacity

Welded sectional and tubular steel, powder coated, with wooden platform. 7 positions for insertable tubular supports. Clearance between supports 90 mm.

2 castor wheels and 2 fixed wheels, castors wheels with wheel lock. **Delivery without tubular supports.**

750 kg = TPE tyres, hubs with groove ball bearing

1200 kg = elasticated solid-rubber tyres, blue-grey „trackless“, hubs with ball bearings.

Loading height: 295 mm

Sheet material stands 4363 | 4365

1200 kg capacity

Welded sectional and tubular steel, powder coated, with wooden platform. 4 rubber feet. 7 positions for insertable tubular supports. **Delivery without tubular supports.** Clearance between tubular supports 90 mm.

One face end fitted with 6-piece pick-up roller.

Pallet feet 2021

As accessory for sheet material stands. Access 100 mm, for pallet truck or fork-lift access.

\*Can not be fitted with FIXSTOP.

	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Outside dimensions L x W x H mm	Net weight kg
Sheet material trolleys for insertable tubular supports (without tubular supports)	4463	750	200	1200 x 800	1320 x 800 x 295	41
	4463-1*	1200	200	1200 x 800	1320 x 800 x 295	46
	4465	750	200	1600 x 800	1720 x 800 x 295	60
	4465-1*	1200	200	1600 x 800	1720 x 800 x 295	66
Sheet material stands (without tubular supports)	4363	1200	-	1200 x 800	1365 x 800 x 100	45
	4365	1200	-	1600 x 800	1765 x 800 x 100	51

	Order no.	Length mm	Height mm	Net weight kg
Insertable tubular supports for sheet material trolleys and for sheet material stands	3012	1200	300	5
	6012	1200	600	6
	9012	1200	900	7,5
	3016	1600	300	6
	6016	1600	600	7
	9016	1600	900	8,5
Pallet feet	2021	-	-	6

Accessories on pages 183-185





### Glass panel trolleys and trolleys for sheet material

for safe transport of glass panels, wood or plastic panels as well as complete windows or doors.

Trolleys for sheet material. Welded sectional and tubular steel. Powder coated blue RAL 5007.

2 swivel and 2 fixed-wheel castors, elasticated solid rubber tyres, blue-grey „trackless“, hubs with ball bearings.

Swivel castors with wheel locks.

For up to 1200 kg capacity.

#### 4454 | 4455 | 4456

One-sided.

Fitted with rubber strip on one side only.

#### 4474 | 4475 | 4476

Double-sided.

Fitted with rubber strip on two sides.



4454 | 4455 | 4456



4474 | 4475 | 4476

Accessories  
on pages 183-185

	Order no.	Capacity kg	Wheel-Ø mm	Outside dimensions L x W x H mm	Loading surface L x W mm	Support height mm	Net weight kg
Sheet material trolleys (one-sided)	4454	1200	200	1276 x 800 x 1788	1276 x 430	1450	66
	4455	1200	200	1676 x 800 x 1788	1676 x 430	1450	74
	4456	1200	200	2076 x 800 x 1788	2076 x 430	1450	99
Sheet material trolleys (double-sided)	4474	1200	200	1276 x 800 x 1783	1276 x 2x 230	1450	72
	4475	1200	200	1676 x 800 x 1783	1676 x 2x 230	1450	80
	4476	1200	200	2076 x 800 x 1783	2076 x 2x 230	1450	103

# TROLLEYS FOR LONG GOODS

**Application:**

Agile trolleys for transporting long goods such as pipes, profiles, bars, rods etc. Capacity 1.5 - 3 tons.

**Removable stanchions:**

For simple loading and unloading.



**Manoeuvrable:**

Can be turned on the spot due to 4 swivel castors or diamond-shaped wheel layout.

**Flooring-friendly:**

Trackless tyres are suitable even for sensitive flooring.

Trolleys for long goods 2110 + 2123





**Trolleys for long goods**

Sectional steel construction, with insertable tubular steel stanchions, powder coated.

**2110**

Platform of anti-slipping, water-proof plywood. 4 heavy duty castor wheels, elasticated solid rubber tyres, blue-grey „trackless“, hubs with ball bearings. 2 castors with wheel lock.



2110

**2111**

2 cradles, centre clear for crane or fork-lift loading. Rhombic arrangement of wheels, on centre 2 fixed wheels, at each end 1 castor wheel with polyurethane tyre 200 x 50 mm. Hubs with ball bearings. Wheel lock on centre axle.



2111

**2113**

2 cradles, centre clear for crane or fork-lift loading. Wheels: on centre axle elasticated solid rubber tyres 360 x 75 mm, at each end 1 castor wheel with elasticated solid rubber tyre 200 x 50 mm, blue-grey „trackless“. Wheel lock on centre axle.



2113

**2123**

As 2113, but wheels with polyurethane tyre.



2123

	Order no.	Capacity kg	Outside dimesions L x W x H mm	Loading height mm	Usef. length of stanchions mm	Clear width mm	Tyres mm	Net weight kg
<b>Trolleys for long goods</b>	2110	1500	700 x 700 x 895	338	550	510	200 x 50	61
	2111	1500	2000 x 600 x 850	350	500	500	200 x 50	74
	2113	2500	2500 x 700 x 920	420	500	600	360 x 75 / 200 x 50	175
	2123	3000	2500 x 700 x 920	420	500	600	360 x 75 / 200 x 50	178