

SACK TRUCKS

Safety handle:

Sturdy handle with safety loop:
Protects the hands from abrasions
and bruises.

Construction:

Inclined frame structure to support
bags and round goods.

**Powder-coated:**

Surface shot-blasted and powder-coated. For long service life and permanent good looks.

**Wheel attachment:**

The fetra wheel in an own design with a displaced hub, no protrusion. Bolted wheel attachment enables easy wheel changes.

**Shovel:**

Available in various sizes and exchangeable.

Sack truck **B1215L**



Sack trucks

Handy tubular steel trucks with steel sheet blades, sturdy welded construction, blue RAL 5007. Safety grips. Steel sheet front shovel mountable, therefore exchangeable. Optionally solid rubber, pneumatic tyres or puncture-proof polyurethane tyres on synthetic rims, hubs with roller bearings.

Flat packed delivery.

Utility patent

20 2004 010 071.1



B1115L



B1116L



B1215L



B1216L

	Order no.	Capacity kg	Height mm	Blade depth mm	Blade width mm	Total width mm	Tyre size mm	Tyres	Net weight kg
Sack trucks	B1115V	250	1150	150	400	590	260 x 56	solid rubber	15
	B1115L	250	1150	150	400	590	260 x 85	pneumatic	12
	B1115P	250	1150	150	400	590	260 x 85	polyurethane	12,7
	B1116V	250	1150	300	480	590	260 x 56	solid rubber	18
	B1116L	250	1150	300	480	590	260 x 85	pneumatic	15
	B1116P	250	1150	300	480	590	260 x 85	polyurethane	15,7
	B1215V	350	1200	150	450	620	260 x 56	solid rubber	19
	B1215L	350	1200	150	450	620	260 x 85	pneumatic	16
	B1215P	300	1200	150	450	620	260 x 85	polyurethane	16,7
	B1216V	350	1200	300	480	620	260 x 56	solid rubber	21
	B1216L	350	1200	300	480	620	260 x 85	pneumatic	18
	B1216P	300	1200	300	480	620	260 x 85	polyurethane	18,7
Handle	1762								with safety loop for tube-Ø 27 mm

Accessories on page 186

ALLIANCE SUPPLIES SDN.BHD.

STACKING TRUCKS



Handling:

Curved top bar and transversal struts. For safe transport of round items such as rolls, cans, buckets etc.


Powder-coated:

Surface shot-blasted and powdercoated. For long service life and permanent good looks.



Safety handle:

Sturdy handle with safety loop: Protects the hands from abrasions and bruises.



Plastic skids:

Easily and at low cost replaceable. The ends of the skids are reinforced and adjoin full flat on the pipe bend.



Shovel:

Available in various sizes and exchangeable.

Wheel attachment:

The fetra wheel in an own design with a displaced hub, no protrusion. Bolted wheel attachment enables easy wheel changes.



Stacking truck **B1330L**



Stacking trucks

Handy tubular steel trucks with steel sheet blades, sturdy welded construction, blue RAL 5007. Safety grips. Steel sheet front shovel mountable, therefore exchangeable.

Optionally solid rubber, pneumatic tyres or puncture-proof polyurethane tyres on synthetic rims, hubs with roller bearings.

Curved top bar and transversal struts. For safe transport of circular items such as rolls, cans, buckets etc.

Flat packed delivery.

Utility patent
20 2004 010 071.1



Example of use pneumatic + solid rubber



B1125L



B1325L



B1326L



Solid rubber tyres



Pneumatic-tyres



PU-tyres



Clamping band 1722G
See page 186.

	Order no.	Capacity kg	Height mm	Blade depth mm	Blade width mm	Total width mm	Tyre size mm	Tyres	Net weight kg
Stacking trucks	B1125V	200	1150	250	320	570	260 x 56	solid rubber	14
	B1125L	200	1150	250	320	570	260 x 85	pneumatic	11
	B1125P	200	1150	250	320	570	260 x 85	polyurethane	11,7
	B1325V	300	1300	250	320	580	260 x 56	solid rubber	17
	B1325L	300	1300	250	320	580	260 x 85	pneumatic	14
	B1325P	300	1300	250	320	580	260 x 85	polyurethane	14,7
	B1326V	300	1300	300	480	580	260 x 56	solid rubber	19
	B1326L	300	1300	300	480	580	260 x 85	pneumatic	16
	B1326P	300	1300	300	480	580	260 x 85	polyurethane	16,7
Handle	1762								with safety loop for tube-Ø 27 mm

Accessories on page 186



B1330L + B1330V

Stacking trucks

Handy tubular steel trucks with steel sheet blades, sturdy welded construction, blue RAL 5007. Safety grips. Steel sheet front shovel mountable, therefore exchangeable.

Optionally solid rubber, pneumatic tyres or puncture-proof polyurethane tyres on synthetic rims, hubs with roller bearings.

Curved top bar and transversal struts. For safe transport of circular items such as rolls, cans, buckets etc.

Flat packed delivery.

Utility patent

20 2004 010 071.1

B1330L | B1331L

With replaceable synthetic rockers.

Wear parts

Plastic skids

1753

1 set with clips.

See page 186.



B1331L



B1327L



B1328L

	Order no.	Capacity kg	Height mm	Blade depth mm	Blade width mm	Total width mm	Tyre size mm	Tyres	Net weight kg
Stacking trucks	B1330V	300	1300	250	320	580	260 x 56	Solid rubber	18
	B1330L	300	1300	250	320	580	260 x 85	Pneumatic	15
	B1330P	300	1300	250	320	580	260 x 85	polyurethane	15,7
	B1331V	300	1300	300	480	580	260 x 56	Solid rubber	20
	B1331L	300	1300	300	480	580	260 x 85	Pneumatic	17
	B1331P	300	1300	300	480	580	260 x 85	polyurethane	17,7
	B1327V	300	1600	250	320	580	260 x 56	Solid rubber	18
	B1327L	300	1600	250	320	580	260 x 85	Pneumatic	15
	B1327P	300	1600	250	320	580	260 x 85	polyurethane	15,7
	B1328V	300	1600	300	480	580	260 x 56	Solid rubber	20
	B1328L	300	1600	300	480	580	260 x 85	Pneumatic	17
	B1328P	300	1600	300	480	580	260 x 85	polyurethane	17,7
Handle	1762	with safety loop for tube-Ø 27 mm							

Accessories on page 186



Alu-Stacking trucks

Aluminium trucks made of tubular aluminium with alu blades, very light and handy to use. Aluminum sheet shovel mountable, therefore exchangeable.

Optionally solid rubber, pneumatic tyres or puncture-proof polyurethane tyres on synthetic rims, hubs with roller bearings.

Curved top bar and transversal struts. For safe transport of circular items such as rolls, cans, buckets etc.

Flat packed delivery.



Example of use pneumatic + solid rubber



A1125L



A1115L



A1116L



Solid rubber tyres



Pneumatic-tyres



PU-tyres



Clamping band 1722G

See page 186.

	Order no.	Capacity kg	Height mm	Blade depth mm	Blade width mm	Total width mm	Tyre size mm	Tyres	Net weight kg
Alu-Stacking trucks	A1125V	150	1150	250	320	570	260 x 56	solid rubber	12
	A1125L	150	1150	250	320	570	260 x 85	pneumatic	9
	A1125P	150	1150	250	320	570	260 x 85	polyurethane	9,7
	A1115V	150	1150	150	400	590	260 x 56	solid rubber	11
	A1115L	150	1150	150	400	590	260 x 85	pneumatic	8
	A1115P	150	1150	150	400	590	260 x 85	polyurethane	8,7
	A1116V	150	1150	300	480	590	260 x 56	solid rubber	12
	A1116L	150	1150	300	480	590	260 x 85	pneumatic	9
	A1116P	150	1150	300	480	590	260 x 85	polyurethane	9,7
Handle	1762	with safety loop for tube-Ø 27 mm							

Accessories on page 186



Alu-Stacking trucks

Aluminium trucks made of tubular aluminium with alu blades, very light and handy to use. Aluminium sheet shovel mountable, therefore exchangeable.

Optionally solid rubber, pneumatic tyres or puncture-proof polyurethane tyres on synthetic rims, hubs with roller bearings.

Curved top bar and transversal struts. For safe transport of circular items such as rolls, cans, buckets etc.

Flat packed delivery.

A1330L | A1331L

With replaceable synthetic rockers.

Wear parts

Plastic skids 1753

1 set with clips.



A1330L + A1330V



A1331L



A1325L



A1326L

	Order no.	Capacity kg	Height mm	Blade depth mm	Blade width mm	Total width mm	Tyre size mm	Tyres	Net weight kg
Alu-Stacking trucks	A1330V	200	1300	250	320	590	260 x 56	solid rubber	12
	A1330L	200	1300	250	320	590	260 x 85	pneumatic	9
	A1330P	200	1300	250	320	590	260 x 85	polyurethane	9,7
	A1331V	200	1300	300	480	590	260 x 56	solid rubber	13
	A1331L	200	1300	300	480	590	260 x 85	pneumatic	10
	A1331P	200	1300	300	480	590	260 x 85	polyurethane	10,7
	A1325V	200	1300	250	320	590	260 x 56	solid rubber	12
	A1325L	200	1300	250	320	590	260 x 85	pneumatic	9
	A1325P	200	1300	250	320	590	260 x 85	polyurethane	9,7
	A1326V	200	1300	300	480	590	260 x 56	solid rubber	13
	A1326L	200	1300	300	480	590	260 x 85	pneumatic	10
	A1326P	200	1300	300	480	590	260 x 85	polyurethane	10,7
Handle	1762	with safety loop for tube-Ø 27 mm							

Accessories on page 186



Stairway trucks

Tubular steel, with lifting blades made of steel sheet, sturdy welded construction, powder coated, blue RAL 5007. Safety handles. Steel sheet front shovel mountable.

Flat packed delivery.

Utility patent

20 2004 010 071.1

Curved top bar and transversal struts. For safe transport of circular items such as rolls, cans, buckets etc.

TK1325 | TK1326

With 2 three-armed wheel spiders, each equipped with 3 TPE tyres 160 mm Ø, hubs with ball bearings.

TK1327 | TK1328

With 2 pneumatic tyres on synthetic rims, hubs with roller bearings and 2 five-armed wheel spiders, each equipped with 5 TPE wheels 125 mm Ø, hubs with bush bearings.

Three-arm wheel spider

With 2 three-armed wheel spiders, advantageous for frequent use on stairs and acceptable ground conditions on flat surface.

Five-arm wheel spider

With 2 pneumatic tyres and 2 five-armed wheel spiders, advantageous for frequent use on bad ground conditions on flat surface and occasional use on stairs.

Wear parts

**Handle
1762**

With safety loop for tube-Ø 27 mm. See page 186.

Accessories on page 186



TK1325




TK1326



TK1327



TK1328



Three-arm wheel spider
TK1325 | TK1326



Five-arm wheel spider
TK1327 | TK1328



Wheel spider lock 1770
Add-on kit for stairway trucks
TK1325 and TK1326. For easy
moving on 2 wheels on flat
surface. Easy self assembly.



Wheel-fixing
screwed wheel fixing, easy
wheel change.

	Order no.	Capacity kg	Height mm	Lifting blade depth mm	Lifting blade width mm	Total width mm	TPE tyres mm	Pneumatic tyres mm	Net weight kg
Stairway trucks	TK1325	200	1300	250	320	590	160 x 40	-	18
	TK1326	200	1300	300	480	590	160 x 40	-	22
	TK1327	200	1300	250	320	590	-	260 x 85	20
	TK1328	200	1300	300	480	590	-	260 x 85	22
Wheel spider lock	1770					for TK1325 and TK1326			
Handle	1762					with safety loop for tube-Ø 27 mm			



AK1325



AK1326



AK1327



AK1328



Three-arm wheel spider
AK1325 | AK1326



Five-arm wheel spider
AK1327 | AK1328



Wheel spider lock 1770
Add-on kit for stairway trucks
AK1325 and AK1326. For easy
moving on 2 wheels on flat
surface. Easy self assembly.



Wheel-fixing
screwed wheel fixing, easy
wheel change.

Aluminium stairway trucks

Aluminium tube with aluminium blades, handy welded construction. Safety handles. Aluminium sheet shovel mountable. Flat packed delivery.

Curved top bar and transversal struts. For safe transport of circular items such as rolls, cans, buckets etc.

AK1325 | AK1326

With 2 three-armed wheel spiders, each equipped with 3 TPE tyres 160 mm Ø, hubs with ball bearings.

AK1327 | AK1328

With 2 pneumatic tyres on synthetic rims, hubs with roller bearings and 2 five-armed wheel spiders, each equipped with 5 TPE wheels 125 mm Ø, hubs with bush bearings.

Three-arm wheel spider

With 2 three-armed wheel spiders, advantageous for frequent use on stairs and acceptable ground conditions on flat surface.

Five-arm wheel spider

With 2 pneumatic tyres and 2 five-armed wheel spiders, advantageous for frequent use on bad ground conditions on flat surface and occasional use on stairs.

	Order no.	Capacity kg	Height mm	Lifting blade depth mm	Lifting blade width mm	Total width mm	TPE tyres mm	Pneumatic tyres mm	Net weight kg
Stairway trucks	AK1325	200	1300	250	320	590	160 x 40	-	14
	AK1326	200	1300	300	480	590	160 x 40	-	15
	AK1327	200	1300	250	320	590	-	260 x 85	15
	AK1328	200	1300	300	480	590	-	260 x 85	16
Wheel spider lock	1770	for AK1325 and AK1326							
Handle	1762	with safety loop for tube-Ø 27 mm							

Accessories on page 186

COMPACT HAND TRUCKS | PARCEL CARTS

One-hand operation:
Ready to use in two steps.



Collapsible blade:
Suitable for large parcels.



Compact hand truck:
Extremely light-weight and handy.

Parcel cart | Compact hand truck **K1331L + 1732**



1730



1732



1735



Easy transport



Fast set-up

Compact hand trucks

First-class aluminium-steel tube-construction with aluminium blade and premium plastic parts.

Non-marking blue-grey polymer wheels, hubs with roller bearings.

Hand grip made of comfortable non-slip material.

Integral elasticated retaining straps and strip for safe transportation. Blade and wheels foldable with one move, retractable grip. Ready to use within a few seconds.

1735

Wheels with pneumatic tyres.

Dimensions folded:

Height x Width x Depth (mm)

1730 = 595 x 390 x 50

1732 = 765 x 488 x 64

1735 = 855 x 660 x 135

Dimensions when fully unfolded:

Height x Width x Depth (mm)

1730 = 1030 x 390 x 450

1732 = 1090 x 488 x 490

1735 = 1190 x 660 x 650



	Order no.	Capacity kg	Height mm	Lifting blade depth mm	Lifting blade width mm	Total width mm	Solid rubber tyres mm	Pneumatic tyres mm	Net weight kg
Compact hand trucks	1730	50	1030	300	385	390	127 x 30	-	3,2
	1732	125	1090	320	480	488	170 x 35	-	5,2
	1735	250	1190	450	595	660	-	220 x 70	12,6



Alu-Compact hand truck „Wuppi“

Very handy and shapely universal truck with collapsible blade. Ergonomic handlebars allow grip positions to be adapted to individual body size and various transport situations and protect hands from scratches and bruises. Curved swing arms for easy transport of round goods.

Very robust and perfectly finished aluminium design with aluminium blade and high-quality plastic parts.

Sturdy pneumatic wheels with ball bearings, can be removed in a few easy steps if necessary. Handlebars made of skin-friendly material.

Due to its compact design and the fact that the blade can be collapsed with a single foot movement, the truck is perfectly suited for mobile use, e.g. to be taken along in a delivery vehicle.

Dimensions with collapsed blade:

Height x width x depth (mm):
1250 x 570 x 275

Dimensions with extended blade:

Height x width x depth (mm):
1250 x 570 x 445

Clamping band for load securing

1722G

Two pieced. By flat loops 100 mm long on both ends very easy to fasten in any position at the truck frame.

Tight end 0,3 m with aluminium belt clamp, lose end 2,5 m.

Due to the asymmetric parting suitable for small and large transport goods.

Holding horns for round goods

1722H

Practical holding horns for stabilising of round goods.

In 3 heights each in pairs plugable. 2 positions possibilities for different radii.

1 set = 2 pieces



1722



Example of use



Example of use



Clamping band 1722G



Clamping band 1722G



Holding horns 1722H



Holding horns 1722H

	Order no.	Capacity kg	Height mm	Lifting blade depth mm	Lifting blade width mm	Total width mm	Pneumatic tyres mm	Net weight kg
Compact hand truck	1722	200	1250	165	425	570	225 x 68	6,7
Clamping band	1722G	compatible for all trucks						
Holding horns	1722H	1 set = 2 pieces (only for 1722)						



Parcel carts

Handy tubular steel trucks with big collapsible lifting blade. Steel sheet front shovel mountable, therefore exchangeable. Sturdy welded construction, powder coated, blue RAL 5007. Curved top bar and transversal struts. For safe transport of circular items such as rolls, cans, buckets etc.

Optionally solid rubber, pneumatic tyres or puncture-proof polyurethane tyres on synthetic rims, hubs with roller bearings.

Flat packed delivery.

Utility patent
20 2004 010 071.1

K1116V | K1116L

With tubular steel blade, depth 150 mm, width 400 mm, and collapsible lifting blade made of tubular steel, depth 500 mm, width 330 mm.

**K1326V | K1326L
K1331V | K1331L**

With tubular steel blade, depth 250 mm, width 320 mm, and collapsible lifting blade made of tubular steel, depth 500 mm, width 250 mm.

K1331V | K1331L

With replaceable plastic skids.

Wear parts

**Handle
1762**

With safety loop for tube-Ø 27 mm. See page 186.

**Plastic skids
1753**

1 set with clips. See page 186.



Wheel-fixing
screwed wheel fixing, easy wheel change.



Shovel fixation
When not in use the collapsible shovel can be fixed.

	Order no.	Capacity kg	Height mm	Lifting blade depth mm	Lifting blade width mm	Total width mm	Tyre size mm	Tyres	Net weight kg
Parcel carts	K1116V	250	1150	150/500	400/330	620	260 x 56	solid rubber	17,5
	K1116L	250	1150	150/500	400/330	620	260 x 85	pneumatic	14,5
	K1116P	250	1150	150/500	400/330	620	260 x 85	polyurethane	15,2
	K1326V	300	1300	250/500	320/250	580	260 x 56	solid rubber	19,5
	K1326L	300	1300	250/500	320/250	580	260 x 85	pneumatic	16,5
	K1326P	300	1300	250/500	320/250	580	260 x 85	polyurethane	17,2
	K1331V	300	1300	250/500	320/250	580	260 x 56	solid rubber	19,5
	K1331L	300	1300	250/500	320/250	580	260 x 85	pneumatic	16,5
	K1331P	300	1300	250/500	320/250	580	260 x 85	polyurethane	17,2

Accessories on page 186



Chair trucks
B1335V | B1335L |
B1335P

For transporting stacked chairs.
 Of tubular construction.

A combination of stacking trolley B1325V | B1325L with chair carrying facility.

Sturdy welded construction, powder coated blue RAL 5007 only. Optionally solid rubber, pneumatic tyres or puncture-proof polyurethane tyres on synthetic rims, hubs with roller bearings

Curved top bar and transversal struts. For safe transport of circular items such as rolls, cans, buckets etc.

The carrying arms are engaged to the trolley and can be continuously adjusted in height.

The carrying arms are covered with protective hoses.

When not in use as a chair trolley the arms will fold back to the main frame so that the trolley can be used for other purposes (as picture).

Carrier arms:
 Depth 500 mm
 Width 250 mm
 Capacity 70 kg

German patent
 10 2004 034 195



B1335L Carrying spar hooked up

Carrying arms put in resting position.



B1345V | B1345L |
B1345P

As B1335V | B1335L | B1335P, but carrier spar can be screwed with clamp to truck.

After loosen the 2 screws the carrier spar can be continuously adjusted in height.

The carrying arms are covered with protective hoses.

Carrier arms:
 Depth 500 mm
 Width 320 mm
 Capacity 70 kg



B1345L Carrying spar screwed with truck



Solid rubber tyres



Pneumatic-tyres



PU-tyres

	Order no.	Capacity kg	Height mm	Lifting blade depth mm	Lifting blade width mm	Total width mm	Tyre size mm	Tyres	Net weight kg
Chair trucks	B1335V	300	1300	250	320	580	260 x 56	solid rubber	19
	B1335L	300	1300	250	320	580	260 x 85	pneumatic	16
	B1335P	300	1300	250	320	580	260 x 85	polyurethane	16,7
	B1345V	300	1300	250	320	580	260 x 56	solid rubber	19
	B1345L	300	1300	250	320	580	260 x 85	pneumatic	16
	B1345P	300	1300	250	320	580	260 x 85	polyurethane	16,7

Accessories on page 186




Example application



11040



11042



Carrier spars 11045 or transport on stairs with 11030 | 11040 | 11042



Clamping band

Trucks for appliances

11040

Truck for transporting appliances, such as stoves, refrigerators, washing machines and dish washers, etc. Sturdy welded tubular steel construction, powder coated in blue RAL 5007. Wide rubber pads and non-slip cover on the blades. Pneumatic tyres. Wheel hubs with roller bearings.

11042

As 11040, but with larger frame height and effective height. Therefore it is possible to transport 2 machines on top of each other.

Accessories

Carrier spars

11045

2 handholds with clamps and wide cross strut, welded, powder coated blue RAL 5007.

Clamping band

11047

For securing the transport goods.

Length 3,30 m, width 25 mm, with quick release fastener.



	Order no.	Capacity kg	Height mm	Lifting blade depth mm	Lifting blade width mm	Total width mm	Pneumatic tyres mm	Net weight kg
Trucks for appliances	11040	350	1150	150	450	650	260 x 85	15
	11042	350	1425	150	450	650	260 x 85	18
Carrier spars	11045	350	850	-	-	570	-	3,2
Clamping band	11047	-	-	-	-	-	-	-

Accessories on page 186



**Trucks for appliances
11050 complete**


Trucks for appliance for the transport of heavy loads, such as boilers on the same level and especially on stairs.

Very sturdy welded tubular steel construction, powder coated in blue RAL 5007.

Wide rubber pads and non-slip cover on the blades.

Complete equipment with:

- Large pneumatic tyres 300 x 100 mm.
- Wheel spiders with 3 TPE tyres each 160 x 40 mm.
- Wheel spiders with 3 blue-grey solid rubber tyres 160 x 40 mm, hubs with roller bearings.
- Pneumatic tyres and wheel spiders can be used alternately on one axle.
- Solid rubber support wheels 160 x 40 mm „trackless“. This makes the truck easy to move when lowered.
- Wheel locks on the support wheels, enabling these to be used as brakes when negotiating stairs.
- The handlebar is height adjustable and can be turned through 180°, enabling it to be properly adjusted for any transport situation.
- Carrier spar.
- Tension belt to secure the load.



11050



Example application

**11051
with pneumatic tyres**

As 11050, but with pneumatic tyres, wheel hubs with roller bearings. No wheel spiders, no carrier spars, no clamping band.

If needed order separately.



11051




11052

**11052
with wheel spiders**

As 11050, but with wheel spiders. No pneumatic tyres. no carrier spars, no clamping band.

If needed order separately.



Carrier spars 11055 for transport on stairs with 11050-11052

11050-11052 with adjusted handlebar



Accessories

Carrier spar 11055

2 handholds with clamps and wide cross strut, welded, powder coated blue RAL 5007.

Clamping band 11057

For securing the transport goods. Length 5 m, width 25 mm, with ratchet closure.

Accessories on page 186

	Order no.	Capacity kg	Height mm	Lifting blade depth mm	Lifting blade width mm	Total width mm	Solid rubber tyres mm	Pneumatic tyres mm	Net weight kg
Truck for appliances with pneumatic tyres, wheel spiders, carrier spar and clamping band	11050	400	1300	190	550	700	-	300 x 100	56
Truck for appliances with pneumatic tyres	11051	400	1300	190	550	700	-	300 x 100	39
Truck for appliances with wheel spiders	11052	400	1300	190	550	700	160 x 40	-	48
Carrier spars	11055	400	890	-	-	600	-	-	6,7
Clamping band	11057	-	-	-	-	-	-	-	-