MEASURING

The torque wrench is the most critical tool in any technician tool box. The specific accurate torque of a fastener is the only way you can be sure not to damage the fastener or have the fastener come loose. At SP Tools we cover a range of products that can produce accurate torque measurements from 6.8Nm to 1000Nm



TORQUE WRENCHES

DIGITAL DISPLAY



REVERSIBLE RATCHET HEAD

Counter Clockwise & Clockwise **Torque Capable**

TORQUE TARGET ALARM

Visual and audible alarm for when torque target is reached

TORQUE WRENCHES - DIGITAL FLEX HEAD. ONE-STEP TOROUE-ANGLE

Strictly for the professional, cutting edge software coupled with load sensing cells and embedded angle encoders, enables one-step Torque-angle measurements. This superbly finished and user friendly tool, has been designed to increase both your speed and accuracy of work.

- Flex Head Ratchet The ultimate in confined space convenience
 Range selection: Nm, in-lb, ft-lb, kg-cm, " ° "
 Calibrated for both Clockwise and Anti-Clockwise use

- Warning LED's and audible alarm sounds within 10% of target value Automatic torque value compensation for flex head angle deviation
- Selectable Torque Functions: Peak mode & Tracking mode
- Angle function: 0° to 360° (+/- 2% accuracy)
- Uses standard or rechargeable AA batteries (easy installation)
- Auto sleep feature after approx. 2 minutes
- Able to measure the undo torque of fasteners
- Housed in high impact blow mould storage case









SOCKET QUICK RELEASE

REVERSIBLE RATCHET HEAD

Counter Clockwise & Clockwise **Torque Capable**

TORQUE TARGET ALARM

Visual and audible alarm for when torque target is reached

TORQUE WRENCHES - DIGITAL

- Digital displayDigital torque value readout
- +/- 2% Accuracy
- Reversible ratchet head counter clockwise & clockwise torque capable
- Peak hold & track mode selectable
- Buzzer & LED indicator for pre-settable target torque
- Range selection: Nm, ft-lb, in-lb, kg-cm
- Quick release mechanism
- Auto sleep after about 5 minutes idle · Supplied in a blow mould heavy duty case
- Batteries included

ı	DRIVE	LENGTH	RANGE	MODEL
	3/8"Dr	425mm	6.8-135Nm	SP35256
	1/2"Dr	535mm	10-200Nm	SP35357
	1/2"Dr	655mm	17-340Nm	SP35358



DIGITAL DISPLAY



AVAILABLE IN 2 SIZES

DRIVE	LENGTH	RANGE	MODE
/2"Dr	530mm	10-200Nm	SP3535
/2"Dr	650mm	17-340Nm	SP3535



CONTINUED TORQUE WRENCHES



REVERSIBLE RATCHET HEAD

Counter Clockwise & Clockwise **Torque Capable**

SOCKET OUICK RELEASE

TORQUE WRENCHES DIGITAL - STUBBY

- Digital display
- Digital torque value readout
- +/- 2% Accuracy
- Reversible ratchet head counter clockwise & clockwise torque capable
- Peak hold & track mode selectable
 Buzzer & LED indicator for pre-settable target torque
- Range selection: Nm, ft-lb, in-lb, kg-cm
- Quick release mechanism
- Auto sleep after about 5 minutes idle · Supplied in a blow mould heavy duty case
- Batteries included

TORQUE TARGET ALARM

Visual and audible alarm for when torque target is reached

AVAILABLE IN 2 SIZES

DRIVE	LENGTH	RANGE	MODE
1/4"Dr	216mm	1-20Nm	SP351
3/8"Dr	290mm	4.2-85Nm	SP3525





EASY TO READ

Convex lens enlarges well defined, bold scale numbering.

SOCKET QUICK RELEASE

REVERSIBLE RATCHET HEAD

Clockwise Torque Only

TORQUE TARGET ALARM

Audible click for when torque target is reached

TORQUE WRENCHES - MICROMETER

- Click type signal alerts user when the required torque is reached
- Reversible ratchet (clock wise torque only) Scale Adjuster - accurate & easy adjustment
- · Adjuster lock will hold required setting during use
- Easy readable scale convex lens enlarges well defined, bold scale numbering. (Nm scale only)
- Quick release mechanism





	DRIVE	LENGTH	RANGE	MODEL
	1/4"Dr	323mm	5-25Nm	SP35152
	3/8"Dr	400mm	20-100Nm	SP35252
	1/2"Dr	517mm	40-200Nm	SP35352
	1/2"Dr	517mm	60-340Nm	SP35353
•	3/4"Dr	918mm	110-550Nm	SP35463
	3/4"Dr	1210mm	150-750Nm	SP35473
	1"Dr	1500mm	200-1000Nm	SP35573





DIGITAL DISPLAY



TORQUE WRENCHES CONTINUED



SOCKET QUICK RELEASE

REVERSIBLE RATCHET HEAD

Counter Clockwise & Clockwise **Torque Capable**

TORQUE TARGET ALARM

Visual, audible and vibration alarm for when torque target is reached

TORQUE WRENCHES - DIGITAL

- Digital display
- Digital torque value readout
 +/- 2% Accuracy
- 50 Data sets of memory capacity
- Reversible ratchet head counter clockwise & clockwise torque capable
- 2 LED indicator for pre-settable target torque • Range selection: Nm, ft-lb, in-lb, kg-cm
- 72 Gear teeth
- Standard functions: Torque, measurement & mode settings.
- Quick release mechanism
- Vibration and audible torque confirmation
- Easy to set up peak or trace modes
- Anti-slip soft grip handle

reliable accuracy

• 8mm shank diameter

Diameter of bezel: 60mm

Easy-to-read crisp graduations

AVAILABLE IN 2 SIZES

DRIVE	LENGTH	RANGE	MODEL
3/8"Dr	380mm	27-135Nm	T835252
1/2"Dr	480mm	40-200Nm	T835355

ANGULAR TORQUE GAUGE



SP35360

ANGULAR TORQUE GAUGE 1/2"DR

- 360° scale (Dial Pointer) Support arm included
- Allows correct tensioning of fasteners by degrees of torque
- This tool is required when manufacturers specify a torque setting using a measurement of degrees after the initial torque is set
- Can be used for all torque-to-yield applications (particularly engine head bolts)

DIAL INDICATOR & MAGNETIC STAND



SP35697

MAGNETIC STAND ADJUSTABLE SUITS DIAL INDICATORS

- Attaches horizontally or vertically to flat surfaces
- V groove base mounting on cylindrical surfaces Suits dial indicators with 4mm or 8mm shafts
- Fine adjust arm and solid knobs
- · Flexible, precise rotary joints adjust any direction
- Powerful magnetic base with on/off switch
- 60kg magnetic pulling force
- . High stability ideal for precision
- measurement applications Note: Dial indicator is not included.




TELESCOPIC GAUGES

TELESCOPIC GAUGE SET 6 PIECE

- Range 8-150mm, 5/16"-6"
 For quick and accurate measurement of bore diameters
- Hardened stainless steel automatic self-centring plungers
- · Locks on any setting by turning knob at the end of the handle
- Spring loaded cylinders
- · Size obtained by measuring over contacts with a micrometer or calliper
- Housed in heavy duty storage case with EVA foam inserts



CALIPERS



100 110 120 130 140 150 160 170 180 190 20

- 4-way measurement Inside, outside, step & depth
- Slider provides smooth, stable and comfortable
- Upper locking screw
- MODEL LENGTH

150mm/6'

200mm/8" SP35608

AVAILABLE IN 2 SIZES

SP35607



VERNIER CALIPERS - DIGITAL

- Available in 2 sizes: 150mm/6" & 200mm/8" Graduation 0.01mm/0.0005'
- 4-way measurement Inside, outside, step & depth · Slider provides smooth, stable and comfortable
- Zero calibration switch with automatic on/off
- Easy to read LCD screen
- Metric & SAE measurement
- Thumb lock adjustment.

LENGTH 150mm/6'

200mm/8"

MODEL SP35631 SP35632



- Measuring face hardened & lapped
- Metric & SAE reading on dial
- 4-way measurement Inside, outside, step & depth
- Shock proof dial • Thumb lock adjustment.
- Hardened stainless stee



STEEL RULERS

STAINLESS STEEL RULERS AVAILABLE IN 4 OPTIONS METRIC/SAE - INDIVIDUAL

- Available in 4 individual sizes: 150mm/6", 300mm/12", 600mm/24" & 1000mm/40"
 High quality hardened stainless steel rulers
- Double sided with hang hole
- Permanently etched graduations in both
- mm and inches
- Satin finish

. x 4 x 6 7 8 8 70 7 7 7 9 9 5 7 8 8 20 7 7 7 7 9 9 8 9 8 9 8 9 9 0 7 7 7 7 9 8 7 8 8 9 0 7 8 8 9 0 7 8 8 9 0 7

LENGTH	MODE
150mm/6"	SP3521
300mm/12"	SP3521
600mm/24"	SP3521
1000mm/40"	SP3521

TAPE MEASURE

© SP Tools Product Catalogue



SP35200

TAPE MEASURE - 8M

- Easy lock and release 20% thicker blade
- 25mm blade width
- Long stand-out
- 3 times longer life span • 3 rivet end hook extends tape life
- Self locking
- Slip-resistant rubber grip
- Steel belt clip

OUTSIDE MICROMETERS

SP35693

OUTSIDE MICROMETER SET 3 PIECE

- Set Includes: 0-25mm, 25-50mm & 50-75mm Micrometers
- Graduation: 0.01mm
- Carbide measuring face
- Setting gauge including ratchet stop Manufacturing standard: DIN863
- Housed in heavy duty storage case with protective foam tray





OUTSIDE MICROMETER - INDIVIDUAL

- Available in 3 individual sizes: 0-25mm, 25-50mm & 75-100mm
- Graduation: 0.01mm
- Carbide measuring face
- Setting gauge including ratchet stop
- Manufacturing standard: DIN863

AVAILABLE IN 3 SIZES


RANGE	MODEL
0-25mm (0.01 reading)	SP35661
25-50mm (0.01 reading)	SP35663
75-100mm (0.01 reading)	SP35667

SPECIALITY TOOLS

> AUTO SPECIALITY

SP Tools offers a wide range of au including mirrors, magnets, pick u just to name a few. Be sure to che p tools and pry bars ck out our latest range of indexing pry bars. A great tool to have when access is limited.

TELESCOPIC INSPECTION MIRRORS



INSPECTION MIRROR TELESCOPIC - OVAL

- Extends from 185mm to 546mm
- Stainless steel inspection tool • 25x50mm mirror
- Swivel head



INSPECTION MIRRORS TELESCOPIC - ROUND

AVAILABLE IN 3 OPTIONS

 Strong & lightweight stainless steel shafts PVC cushion handle

EXTENDABLE LENGTH MODEL MIRROR DIA. SP31401 32mm 203 to 889mm SP31402 57mm 250 to 930mm 82mm 280 to 800mm SP31403

INSPECTION MIRROR & PICK UP TOOL SET

