

PIGTAIL

- ✓ **Pigtail basically used to splice the fiber in the cable so that can connect to patch panel or equipment**
- ✓ **Various fiber type, cable and connector option**
- ✓ **Compliance with Telecordia,ANSI,IEC, TIA/EIA**



SC PIGTAIL



FC PIGTAIL



LC PIGTAIL

DESCRIPTION	CLM5-SM-PGTL-SC/UPC	CLM5-SM-PGTL-LC/UPC	CLM5-SM-PGTL-FC/UPC
	SC/UPC Singlemode Pigtail	LC/UPC Singlemode Pigtail	FC/UPC Singlemode Pigtail
CONNECTOR TYPE	SC/UPC	LC/UPC	FC/UPC
FIBER TYPE	Singlemode	Singlemode	Singlemode
INSERT LOSS	≤ 0.30dB	≤ 0.30dB	≤ 0.30dB
RETURN LOSS	≥ 50dB	≥ 50dB	≥ 50dB
DURABILITY (500 matings)	-2.0dB	-2.0dB	-2.0dB
OPERATIONAL TEMPERATURE	- 20~ + 40 °	- 20~ + 40 °	- 20~ + 40 °
LENGTH (meter)	2	2	2
CABLE OVERALL DIAMETER(mm)	≈ 0.9	≈ 0.9	≈ 0.9
FIBER CLASS	G.652.D (OS1,OS2)	G.652.D (OS1,OS2)	G.652.D (OS1,OS2)



Closed-Loop Industries SDN. BHD

NO. 28 & 30, Jalan TS 6/7, Taman Perindustrian Subang,
Taman Indah Subang Uep, 47150 Subang Jaya,
Selangor Darul Ehsan.
+603 - 8081 2216