HS-AS Studs mounting/grub screws



Screw studs for use to adapt a female thread into a male thread.

Mounting Studs provide a secure, permanent or semi-permanent point of connection.

Unless stated all studs are Stainless Steel.

| Part No. | Connection Point 1 | Connection Point 2 | | | |
|----------|---------------------------|--|-----|---------|--|
| HS-AS008 | 1/4"-28 UNF Male | M8 Male x 1.25 Stop & Slot x 11.5mm Long | (1) | Man | |
| HS-AS020 | 10-32 UNF x 9.5 mm Long I | Male Hex Socket Drive | 1 | 1 | |
| HS-AS021 | 1/4"-28 UNF Male | M10 Male x 1.50 Stop & Slot x 11.5mm Long | 4 | | |
| HS-AS022 | 1/4"-28 UNF Male | 1/4"-28 UNF Male Stop & Slot x 11.5mm Long | | | |
| HS-AS023 | 1/4"-28 UNF Male | M8 Male x 1.25 x 8mm Long | | | |
| HS-AS024 | 1/4"-28 UNF Male | M6 Male x 1 Stop & Slot x 11.5mm Long | No. | | |
| HS-AS025 | 1/4"-28 UNF Male | 3/8"-24 UNF Male x 14mm Overall Length | 8 | • | |
| HS-AS043 | 1/4"-28 UNF Male | 10-32 UNF Male x 10mm Long | 8 | | |
| HS-AS053 | 1/4"-28 UNF Male | M6 Male x 1mm x 10mm Long | | | |
| HS-AS076 | ½"-20 UNF Male | M6 Male with Screwdriver Slot x 8mm | | | |
| HS-AS081 | 1/4"-28 UNF Male | M12 Male x 1.7 x 15mm Overall Length | | Annua (| |
| HS-AS083 | 1/4"-28 UNF Male | M10 Male x 1.5 x 12mm Long | | | |





HS-AS Studs mounting/grub screws

| Part No. | Connection Point 1 | Connection Point 2 | | | |
|----------|---------------------------|---|--|---|-------|
| | | | | | |
| HS-AS084 | 1/4"-28 UNF Male | M5 Male x 0.8 x 10 mm Long | | | |
| | | | | | |
| HS-AS086 | 1/4"-28 UNF Male | M8 x 1 Male Stop & Slot x 11.5mm Long | 1 | 1 | |
| | | | | | |
| HS-AS090 | 1/4"-28 UNF Male | M10 x 1.25 Male x 10mm Long | | 1 | |
| | | | | | |
| HS-AS101 | 1/4"-28 UNF Male | ½"-20 UNF Male with Screwdriver Slot x 8mm Long | 3 | 0 | |
| | | | | | |
| HS-AS102 | 1/4"-28 UNF Male | ½"-20 UNF Male with Screwdriver Slot x 8mm Long | | 0 | Brass |
| | | | | | |
| HS-AS104 | 1/4"-28 UNF Male | M6 Male x 1 x 7.5mm Long | ALL OF THE PARTY O | | |
| | | | 6 | | |
| HS-AS110 | 1/4"-28 UNF Male | M10 x 1.25 Male x 12mm Long | | | |
| | | | | | |
| HS-AS112 | 1/4"-28 UNF Male | M12 x 1.5 Male x 17mm Long | | | |
| | | | | | |
| HS-AS115 | 1/4"-28 UNF Male | 1/2" - 13 TPI UNC x 1" Male | | | |
| | | | | | |
| HS-AS122 | 1/4"-28 UNF Male | M10 x 1 Male Stop & Slot x 12mm Long | 1 | 1 | |
| | | | | | |
| HS-AS208 | 1/4"-28 UNF x 12.7mm Long | g Male Hex Socket Drive | | | |



